

<b>TEST REPORT</b> <b>IEC 60335-2-84</b> <b>Safety of household and similar electrical appliances</b> <b>Part 2: Particular requirements for toilets</b>	
Report Reference No. ....:	CPSA0122762
Date of issue .....	2012-07-04
Total number of pages .....	10 pages and attachment 2 pages
Appendix to Test Report Reference No.:	CPSA0115682
Modification to the appliance.....:	-Alternative components: dry fan motor, deodorization fan motor -Typo correction for flow select stepping motor -Evaluation for amendment A15:2011 to EN 60335-1:2002
Modification to clause.....:	cl. 13, cl.19.7, cl. 24
Page concerned.....:	10, 11, 14, 15, 28, 61 – 64 , attachment 1
Testing Laboratory.....:	TÜV SÜD Korea Laboratory (TKL)
Address .....	#315 and 316, MARIO Tower, 222-12, Guro-Dong, Guro-Gu, 152-050, Seoul, Republic of Korea
Applicant's name.....:	HYUNDAI WacorTec. Co., Ltd.
Address .....	684-49, Gongreung-Dong, Nowon-Ku, Seoul 139-808 Republic of Korea
<b>Test specification:</b>	
Standard.....:	IEC 60335-2-84 2002 (Second edition) + A1:2008 with IEC 60335-1:2001 (Fourth ed.) (incl. Corr.1:2002) + A1:04 + A2:06 (incl. Corr. 1:2006)
Test procedure .....	CE LVD
Non-standard test method.....:	N/A
Test Report Form No. ....:	IEC60335_2_84B
Test Report Form(s) Originator.....:	LCIE.
Master TRF .....	Dated 2008-06
<b>Copyright © 2008 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.</b> This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. If this Test Report Form is used by non-IECEE members, the IECEE/IEC logo and the reference to the CB Scheme procedure shall be removed. <b>This report is not valid as a CB Test Report unless signed by an approved CB Testing Laboratory and appended to a CB Test Certificate issued by an NCB in accordance with IECEE 02.</b>	
Test item description .....	Sanitary Equipment (Electric Bidet Seats)
Trade Mark .....	N/A
Manufacturer .....	Same as applicant
Model/Type reference .....	DIB-2000, HDB-1500R, HDB-1500, HDB-1300, HDB-1100, HDB-2500R, HDB-2500, HDB-2300
Ratings .....	220-240 V~, 50/60 Hz, 1670 W, IPX4, Class I

<b>Testing procedure and testing location:</b>	
<input checked="" type="checkbox"/> <b>Testing Laboratory:</b>	TÜV SÜD Korea Laboratory (TKL)
Testing location/ address .....	#315 and 316, MARIO Tower, 222-12, Guro-Dong, Guro-Gu, 152-050, Seoul, Republic of Korea
<input type="checkbox"/> <b>Associated CB Laboratory:</b>	
Testing location/ address .....	N/A
Tested by (name + signature).....	Charles Im <i>Charles Im</i>
Approved by (+ signature).....	Brian Cha <i>Brian Cha</i>
<input type="checkbox"/> Testing procedure: TMP	
Tested by (name + signature).....	N/A
Approved by (+ signature).....	N/A
Testing location/ address .....	N/A
<input type="checkbox"/> Testing procedure: WMT	
Tested by (name + signature).....	N/A
Witnessed by (+ signature).....	N/A
Approved by (+ signature).....	N/A
Testing location/ address .....	N/A
<input type="checkbox"/> Testing procedure: SMT	
Tested by (name + signature).....	N/A
Approved by (+ signature).....	N/A
Supervised by (+ signature).....	N/A
Testing location/ address .....	N/A
<input type="checkbox"/> Testing procedure: RMT	
Tested by (name + signature).....	N/A
Approved by (+ signature).....	N/A
Supervised by (+ signature).....	N/A
Testing location/ address .....	N/A

**Summary of testing:**

**-Modification 1 Report:**

The original test report ref. no. CPSA0115682, dated 2012-04-18 is modified on 2012-07-04 to include the following change:

- 1) typo correction for flow select stepping motor: see appended table 24.1
- 2) addition of alternative dry fan motor and deodorization fan motor: see appended table 24.1
- 3) evaluation fir amendment A15:2011 to EN 60335-1:2002; see attachment 1 report




-Attachment 1: Amendment A15:2011 to EN 60335-1:2002 (2 pages)

- This report should be read in conjunction with CE LVD test report ref. no. CPSA0115682, dated 2012-04-18, CE LVD AoC no. N8 12 05 58097 008 dated 2012-05-04.
- Test sub clause 13 and 19.7 were conducted on model HDB-1500R.

-The item tested were found to be in compliance with the test standards of EN 60335-2-84:2003 + A1:2008 used in conjunction with EN 60335-1:2002 + A11:2004 + A1: 2004 +A12:2006 +A2:2006 + A13:2008 + A14:2010 + A15:2011 and EN 62233:2008

**Summary of compliance with National Differences: N/A**

**Copy of marking plate:**



<b>Test item particulars</b> .....	Sanitary Equipment (Electric Bidet Seats)
Classification of installation and use .....	Fixed appliance
Supply Connection .....	Power supply cord with plug, Y-attachment
.....	:
.....	:
<b>Possible test case verdicts:</b>	
- test case does not apply to the test object .....	N/A
- test object does meet the requirement .....	P (Pass)
- test object does not meet the requirement .....	F (Fail)
<b>Testing</b> .....	
Date of receipt of test item .....	2012-06-26
Date (s) of performance of tests .....	2012-06-28 to 2012-07-03
<b>General remarks:</b>	
<p>The test results presented in this report relate only to the object tested.  This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.  "(See Enclosure #)" refers to additional information appended to the report.  "(See appended table)" refers to a table appended to the report.</p> <p>Throughout this report a comma (point) is used as the decimal separator.</p>	
<b>General product information:</b>	
<b>Model Differences - The followings are model difference;</b>	
1.Model DIB-2000 is basic model.	
2.Model HDB-1500R are identical to the basic model DIB-2000 except for model designation.	
3.Model HDB-1500 is similar to the basic model DIB-2000 except that it is not equipped with remote control function.	
4. Model HDB-1300 is similar to the basic model HDB-1500 except that it is not equipped with deodorization function.	
5.Model model HDB-1100 is similar to the basic model HDB-1500 except that it is not equipped with deodorization function and dry function.	
6.Model HDB-2500R are similar to the basic model DIB-2000 except it is equipped with Air Pump Motor instead of Water pump motor.	
7.Model HDB-2500 is similar to the basic model HDB-2500R except that it is not equipped with remote control function.	
8.Model HDB-2300 is similar to the basic model HDB-2500 except that it is not equipped with deodorization function.	

## IEC 60335-2-84

13	LEAKAGE CURRENT AND ELECTRIC STRENGTH AT OPERATING TEMPERATURE		-
13.1	Leakage current not excessive and electric strength adequate		P
	Heating appliances operated at 1.15 times rated power input .....		N/A
	Motor-operated appliances and combined appliances supplied at 1.06 times rated voltage .....	254.4 V	P
	Protective impedance and radio interference filters disconnected before carrying out the tests		N/A
13.2	Leakage current measured by means of the circuit described in figure 4 of IEC 60990		P
	Leakage current measurements	(see appended table)	P
13.3	The appliance is disconnected from the supply		P
	Electric strength tests according to table 4	(see appended table)	P
	No breakdown during the tests		P

19	ABNORMAL OPERATION		-
19.1	The risk of fire or mechanical damage under abnormal or careless operation obviated		P
	Electronic circuits so designed and applied that a fault will not render the appliance unsafe		P
	Appliances incorporating contactors or relays subjected to the test of 19.14, being carried out before the tests of 19.11		P
	Appliances incorporating a automatic controls are also subjected to the test of 19.101 (IEC 60335-2-84)		P
19.7	Stalling test by locking the rotor if the locked rotor torque is smaller than the full load torque or locking moving parts of other appliances		P
	Locked rotor, motor capacitors open-circuited or short-circuited, if required	No motor capacitors	N/A
	Locked rotor, capacitors open-circuited one at a time		N/A
	Test repeated with capacitors short-circuited one at a time, if required		N/A
	Appliances with timer or programmer supplied with rated voltage for each of the tests, for a period equal to the maximum period allowed		P
	Other appliances supplied with rated voltage for a period as specified		P

## IEC 60335-2-84

	Winding temperatures not exceeding values specified in table 8	(see appended table)	P
--	--	----------------------	---

24	COMPONENTS		-
24.1	Components comply with safety requirements in relevant IEC standards		P
	List of components	(see appended table)	P
	Components not tested and found to comply with relevant IEC standard, components not marked or not used in accordance with its marking, tested under the conditions occurring in the appliance		P

## IEC 60335-2-84

13.2	TABLE: Leakage current		P
	Heating appliances: 1.15 x rated input .....	-	—
	Motor-operated and combined appliances: 1.06 x rated voltage.....	254.4 V	—
Leakage current between		I (mA)	Max. allowed I (mA)
L/N and Water		0.08	0.25
L/N and Non-metallic enclosure		0.01	0.25

13.3	TABLE: Electric strength		P
Test voltage applied between:		Voltage (V)	Breakdown (Yes/No)
Basic insulation		1000	No
Reinforced insulation		3000	No

19.7	TABLE: Abnormal operation, locked rotor/moving parts					P
	Test voltage (V) .....	240 V			—	
	Ambient, t <sub>1</sub> (°C).....	1) 22.0 °C, 2) 20.8 °C			—	
	Ambient, t <sub>2</sub> (°C).....	1) 20.3 °C, 2) 19.1 °C			—	
Temperature of winding		R <sub>1</sub> (Ω)	R <sub>2</sub> (Ω)	dT (K)	T (°C)	Max. T (°C)
1) alt.) dry fan motor		-	-	-	70.0	150
2) alt.) deodorization fan motor		-	-	-	93.8	150

24.1	TABLE: Components					P
Object / part No.	Manufacturer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity	
Alt.) deodorization fan motor	J.C. INTERNATIONAL INC.	BFL7530S	DC12 V, 0,30 A 2000 RPM, Class 105 (A)	EN 60335-1 EN 60335-2-84	Tested in appliance	
☞ Flow select stepping motor (Water valve stepping motor)	Leili Electrical Equipment Co., Ltd.	24BYJ48- 144W	12 V dc, 70 Ohms, Class 105 (A)	EN 60335-1 EN 60335-2-84	Tested in appliance	
<b>Dry assembly</b>						
Alt.) dry fan motor	J.C. INTERNATIONAL INC.	BFH7530S	DC12 V, 0,50 A 3800 RPM, Class 105 (A)	EN 60335-1 EN 60335-2-84	Tested in appliance	
1) An asterisk indicates a mark which assures the agreed level of surveillance						

IEC 60335-2-84

Photos


Dry fan motor





IEC 60335-2-84

Deodorization fan motor



IEC 60335-2-84

Photos

Flow select stepping motor (water valve stepping motor)



-End of Test Report-

# Attachment No. 1

**Amendment A15:2011 to EN 60335-1:2002**

**Household and similar electrical appliances – Safety  
Part 1: General requirements**

***Attachment contains***

Cover page:	1 page
Requirements:	1 page
Total:	2 pages

Explanation for Abbreviations:

Possible Verdicts: **P** = Pass, **F** = Fail, **N/A** = Not Applicable

Remarks:

Throughout this report, a comma (point) is used as the decimal separator.

Amendment A15:2011 to EN 60335-1:2002			
Clause	Requirement - Test	Result - Remark	Verdict
<b>25</b>	<b>Supply connection and external flexible cords</b>		-
25.7	Add the following text after the last dash and before the paragraph regarding "Supply cords for class III appliances":		-
	- Halogen-free thermoplastic compound sheathed. Their properties shall be at least those of		N/A
	• halogen-free thermoplastic compound sheathed cords (code designation HO3ZIZIH2-F, HO3Z1Z1-F), for appliances having a mass not exceeding 3 kg;		N/A
	• halogen-free thermoplastic compound sheathed cords (code designation HO5Z1Z1H2-F or HO5Z1Z1-F), for other appliances;		N/A
	- Cross-linked halogen-free compound sheathed. Their properties shall be at least those of cross-linked halogen-free compound sheathed cords (code designation HO7ZZ-F).		N/A
<b>ZC</b>	<b>ANNEX ZC (NORMATIVE)</b> NORMATIVE REFERENCES TO INTERNATIONAL PUBLICATIONS WITH THEIR CORRESPONDING EUROPEAN PUBLICATIONS		-
	A list of referenced documents in this standard		P

- End of Test Report -

**TEST REPORT**  
**IEC 60335-2-84**  
**Safety of household and similar electrical appliances**  
**Part 2: Particular requirements for toilets**

**Report Reference No.**.....: CPSA0115682  
**Date of issue**.....: 2012-04-18  
**Total number of pages** .....: 91 pages and attachment 17 pages

**Testing Laboratory**.....: TÜV SÜD Korea Laboratory (TKL)  
**Address** .....: #315 and 316, MARIO Tower, 222-12, Guro-Dong, Guro-Gu,  
152-050, Seoul, Republic of Korea

**Applicant's name**.....: HYUNDAI WacorTec. Co., Ltd.  
**Address** .....: 684-49, Gongreung-Dong, Nowon-Ku, Seoul 139-808  
Republic of Korea

**Test specification:**  
**Standard**.....: IEC 60335-2-84 2002 (Second edition) + A1:2008 with  
IEC 60335-1:2001 (Fourth ed.) (incl. Corr.1:2002) + A1:04 + A2:06  
(incl. Corr. 1:2006)  
**Test procedure** .....: CE LVD  
**Non-standard test method**.....: N/A

**Test Report Form No.**.....: IEC60335\_2\_84B  
**Test Report Form(s) Originator** .....: LCIE.  
**Master TRF** .....: Dated 2008-06

**Copyright © 2008 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.**



This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

If this Test Report Form is used by non-IECEE members, the IECEE/IEC logo and the reference to the CB Scheme procedure shall be removed.

**This report is not valid as a CB Test Report unless signed by an approved CB Testing Laboratory and appended to a CB Test Certificate issued by an NCB in accordance with IECEE 02.**

**Test item description** .....: Sanitary Equipment (Electric Bidet Seats)  
**Trade Mark** .....: N/A  
**Manufacturer** .....: Same as applicant  
**Model/Type reference**.....: DIB-2000, HDB-1500R, HDB-1500, HDB-1300, HDB-1100,  
HDB-2500R, HDB-2500, HDB-2300  
**Ratings** .....: 220-240 V~, 50/60 Hz, 1670 W, IPX4, Class I






<b>Testing procedure and testing location:</b>	
<input checked="" type="checkbox"/> <b>Testing Laboratory:</b>	TÜV SÜD Korea Laboratory (TKL)
Testing location/ address .....	#315 and 316, MARIO Tower, 222-12, Guro-Dong, Guro-Gu, 152-050, Seoul, Republic of Korea
<input type="checkbox"/> <b>Associated CB Laboratory:</b>	
Testing location/ address .....	N/A
Tested by (name + signature) .....	Charles Im 
Approved by (+ signature) .....	Brian Cha 
<input type="checkbox"/> Testing procedure: TMP	
Tested by (name + signature) .....	N/A
Approved by (+ signature) .....	N/A
Testing location/ address .....	N/A
<input type="checkbox"/> Testing procedure: WMT	
Tested by (name + signature) .....	N/A
Witnessed by (+ signature) .....	N/A
Approved by (+ signature) .....	N/A
Testing location/ address .....	N/A
<input type="checkbox"/> Testing procedure: SMT	
Tested by (name + signature) .....	N/A
Approved by (+ signature) .....	N/A
Supervised by (+ signature) .....	N/A
Testing location/ address .....	N/A
<input type="checkbox"/> Testing procedure: RMT	
Tested by (name + signature) .....	N/A
Approved by (+ signature) .....	N/A
Supervised by (+ signature) .....	N/A
Testing location/ address .....	N/A

**Summary of testing:**

-All tests were conducted on model DIB-2000 and HDB-2500R.  
 -Attachment 1: Amendment A14:2010 to EN 60335-1:2002 (11 pages)  
 -Attachment 2: EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES (6 pages)  
 -EMF test result according to EN 62233:2008 included in attachment 1 test report.  
  
 -The item tested were found to be in compliance with the test standards of EN 60335-2-84:2003 + A1:2008 used in conjunction with EN 60335-1:2002 + A11:2004 + A1: 2004 +A12:2006 +A2:2006 + A13:2008 + A14:2010 and EN 62233:2008

**Summary of compliance with National Differences: N/A**

**Copy of marking plate:**



<b>Test item particulars</b> .....	Sanitary Equipment (Electric Bidet Seats)
Classification of installation and use .....	Fixed appliance
Supply Connection.....	Power supply cord with plug, Y-attachment
.....	:
.....	:
<b>Possible test case verdicts:</b>	
- test case does not apply to the test object.....	N/A
- test object does meet the requirement .....	P (Pass)
- test object does not meet the requirement .....	F (Fail)
<b>Testing</b> .....	
Date of receipt of test item .....	2011-12-01
Date (s) of performance of tests .....	2011-12-02 to 2012-01-20
<b>General remarks:</b>	
<p>The test results presented in this report relate only to the object tested.  This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.  "(See Enclosure #)" refers to additional information appended to the report.  "(See appended table)" refers to a table appended to the report.</p> <p>Throughout this report a <del>comma</del> (point) is used as the decimal separator.</p>	
<b>General product information:</b>	
<b>Model Differences - The followings are model difference;</b>	
1.Model DIB-2000 is basic model.	
2.Model HDB-1500R are identical to the basic model DIB-2000 except for model designation.	
3.Model HDB-1500 is similar to the basic model DIB-2000 except that it is not equipped with remote control function.	
4. Model HDB-1300 is similar to the basic model HDB-1500 except that it is not equipped with deodorization function.	
5.Model model HDB-1100 is similar to the basic model HDB-1500 except that it is not equipped with deodorization function and dry function.	
6.Model HDB-2500R are similar to the basic model DIB-2000 except it is equipped with Air Pump Motor instead of Water pump motor.	
7.Model HDB-2500 is similar to the basic model HDB-2500R except that it is not equipped with remote control function.	
8.Model HDB-2300 is similar to the basic model HDB-2500 except that it is not equipped with deodorization function.	



IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
5	GENERAL CONDITIONS FOR THE TESTS		-
	Tests performed according to cl. 5, e.g. nature of supply, sequence of testing, etc.		P
6	CLASSIFICATION		-
6.1	Appliances incorporating water heaters having bare heating element shall be class I or class III (IEC 60335-2-84):	No such heaters	N/A
6.2	Protection against harmful ingress of water	IPX4	P
	Toilets and heated seats shall be at least IP X4 (IEC 60335-2-84)		P
7	MARKING AND INSTRUCTIONS		-
7.1	Rated voltage or voltage range (V) .....	220-240 V	P
	Nature of supply.....	~	P
	Rated frequency (Hz) .....	50/60 Hz	P
	Rated power input (W) .....	1670 W	P
	Rated current (A) .....		N/A
	Single-phase appliances: 230V covered		P
	Multi-phase appliance: 400V covered:	Single-phase	N/A
	Manufacturer's or responsible vendor's name, trademark or identification mark.....	HYUNDAI WacorTec. Co., Ltd	P
	Model or type reference .....	DIB-2000, HDB-1500R, HDB-1500, HDB-1300, HDB-1100, HDB-2500R, HDB-2500, HDB-2300	P
	Symbol 5172 of IEC 60417, for Class II appliances	Class I	N/A
	IP number, other than IPX0.....	IPX4	P
	Symbol IEC 60417-5036, for the enclosure of electrically-operated water valves in external hose-sets for connection of an appliance to the water mains		N/A
7.2	Warning for stationary appliances for multiple supply		N/A
	Warning placed in vicinity of terminal cover		N/A
7.3	Range of rated values marked with the lower and upper limits separated by a hyphen		P
	Different rated values marked with the values separated by an oblique stroke		N/A
7.4	Appliances adjustable for different rated voltages, the voltage setting is clearly discernible		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
7.5	Appliances with more than one rated voltage or one or more rated voltage ranges, marked with rated input or rated current for each rated voltage or range, unless		N/A
	the power input is related to the arithmetic mean value of the rated voltage range		P
	Relation between marking for upper and lower limits of rated power input or rated current and voltage is clear		N/A
7.6	Correct symbols used	V, ~, Hz, W, 5019 of IEC 60417, kPa, IPX4	P
7.7	Connection diagram fixed to appliances to be connected to more than two supply conductors and appliances for multiple supply		N/A
7.8	Except for type Z attachment, terminals for connection to the supply mains indicated as follows:		-
	- marking of terminals exclusively for the neutral conductor (N)		N/A
	- marking of protective earthing terminals (symbol 5019 of IEC 60417)		P
	- marking not placed on removable parts		P
7.9	Marking or placing of switches which may cause a hazard		P
7.10	Indications of switches on stationary appliances and controls on all appliances by use of figures, letters or other visual means .....	Letters, figures	P
	The figure 0 indicates only OFF position, unless no confusion with the OFF position		N/A
7.11	Indication for direction of adjustment of controls	$\Delta$ , $\nabla$ , +, -	P
7.12	Instructions for safe use provided		P
	The instructions for use shall state how to empty and clean the toilet safely. (IEC 60335-2-84)		P
	They shall include details about final disposal.		N/A
	Unless the toilet is connected to the sewage system		N/A
7.12.1	Sufficient details for installation supplied		P
	The installation instructions of class 0I appliances and class I appliances shall state they have to be earthed (IEC 60335-2-84)		P
	The installation instructions for appliances incorporating water heaters having bare heating elements shall state the substance of the following (IEC 60335-2-84):		-
	-the resistivity of the water supply must not be less than ... $\Omega$ cm:	No such heaters	N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	-the appliance must be permanently connected to fixed wiring.		N/A
	Label concerning glowing cigarettes is to be fixed in a conspicuous place beside the toilet (IEC 60335-2-84)		N/A
7.12.2	Stationary appliances not fitted with means for disconnection from the supply mains having a contact separation in all poles that provide full disconnection under overvoltage category III, the instructions state that means for disconnection must be incorporated in the fixed wiring in accordance with the wiring rules	Fixed appliance	N/A
7.12.3	Insulation of the fixed wiring in contact with parts exceeding 50 K during clause 11; instructions stating that the fixed wiring must be protected		N/A
7.12.4	Instructions for built-in appliances:		-
	- dimensions of space		N/A
	- dimensions and position of supporting means		N/A
	- distances between parts and surrounding structure		N/A
	- dimensions of ventilation openings and arrangement		N/A
	- connection to supply mains and interconnection of separate components		N/A
	- allow disconnection of the appliance after installation, by accessible plug or a switch in the fixed wiring, unless		N/A
	a switch complying with 24.3		N/A
7.12.5	Replacement cord instructions, type X attachment with a specially prepared cord		N/A
	Replacement cord instructions, type Y attachment		P
	Replacement cord instructions, type Z attachment		N/A
7.12.6	Caution in the instructions for heating appliances with a non-self-resetting thermal cut-out		P
7.12.7	Instructions for fixed appliances stating how the appliance is to be fixed		P
7.12.8	Instructions for appliances connected to the water mains:		-
	- max. inlet water pressure (Pa).....:	735.5 kPa	P
	- min. inlet water pressure, if necessary (Pa) .....	68.6 kPa	P
	Instructions concerning new and old hose-sets for appliances connected to the water mains by detachable hose-sets		P

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
7.13	Instructions and other texts in an official language	English version checked	P
7.14	Marking clearly legible and durable		P
7.15	Marking on a main part		P
	Marking clearly discernible from the outside, if necessary after removal of a cover		P
	For portable appliances, cover can be removed or opened without a tool		N/A
	For stationary appliances, name, trademark or identification mark and model or type reference visible after installation		N/A
	For fixed appliances, name, trademark or identification mark and model or type reference visible after installation according to the instructions	On rating label	P
	Indications for switches and controls placed on or near the components. Marking not on parts which can be positioned or repositioned in such a way that the marking is misleading		P
7.16	Marking of a possible replaceable thermal link or fuse link clearly visible with regard to replacing the link		N/A
7.101	Toilets shall be provided with a label stating that glowing cigarettes and other burning materials must not be thrown into the toilet (IEC 60335-2-84)		N/A
	The label shall be suitable for permanent fixing		N/A
8	PROTECTION AGAINST ACCESS TO LIVE PARTS		-
8.1	Adequate protection against accidental contact with live parts		P
8.1.1	Requirement applies for all positions, detachable parts removed		P
	Insertion or removal of lamps, protection against contact with live parts of the lamp cap	No lamp	N/A
	Use of test probe B of IEC 61032: no contact with live parts		P
	Test probe 18 of IEC 61032 is also applied, as specified for test probe B (IEC 60335-2-84)		P
8.1.2	Use of test probe 13 of IEC 61032 through openings in class 0 appliances and class II appliances / constructions: no contact with live parts		P
	Test probe 13 also applied through openings in earthed metal enclosures having a non-conductive coating: no contact with live parts		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
8.1.3	For appliances other than class II, use of test probe 41 of IEC 61032: no contact with live parts of visible glowing heating elements	No visible glowing heating elements	N/A
8.1.4	Accessible part not considered live if:		-
	- safety extra-low a.c. voltage: peak value not exceeding 42.4 V		N/A
	- safety extra-low d.c. voltage: not exceeding 42.4 V		N/A
	- or separated from live parts by protective impedance		N/A
	If protective impedance: d.c. current not exceeding 2 mA, and		N/A
	a.c. peak value not exceeding 0.7 mA		N/A
	- for peak values over 42.4 V up to and including 450 V, capacitance not exceeding 0,1 $\mu$ F		N/A
	- for peak values over 450 V up to and including 15 kV, discharge not exceeding 45 $\mu$ C		N/A
	- for peak values over 15kV, the energy in the discharge not exceeding 350 mJ		N/A
8.1.5	Live parts protected at least by basic insulation before installation or assembly:		-
	- built-in appliances		N/A
	- fixed appliances		P
	- appliances delivered in separate units		N/A
8.2	Class II appliances and constructions constructed so that there is adequate protection against accidental contact with basic insulation and metal parts separated from live parts by basic insulation only		P
	Only possible to touch parts separated from live parts by double or reinforced insulation		P
	Compliance is checked by inspection and applying test probe B of IEC 61032 in accordance with the conditions specified in 8.1.1		P
	Test probe 18 of IEC 61032 is also applied, as specified for test probe B (IEC 60335-2-84)		P
10	POWER INPUT AND CURRENT		-
10.1	Power input at normal operating temperature, rated voltage and normal operation not deviating from rated power input by more than shown in table 1	(see appended table)	P
10.2	Current at normal operating temperature, rated voltage and normal operation not deviating from rated current by more than shown in table 2	(see appended table)	N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	Test for an appliance with one or more rated voltage ranges		N/A
11	HEATING		-
11.1	No excessive temperatures in normal use		P
11.2	Placing and mounting of appliance as described		P
11.3	Temperature rises, other than of windings, determined by thermocouples		P
	Temperature rises of windings determined by resistance method, unless		N/A
	the windings makes it difficult to make the necessary connections		P
11.4	Heating appliances operated under normal operation at 1.15 times rated power input .....		N/A
11.5	Motor-operated appliances operated under normal operation at most unfavourable voltage between 0.94 and 1.06 times rated voltage .....		N/A
11.6	Combined appliances operated under normal operation at most unfavourable voltage between 0.94 and 1.06 times rated voltage .....	206.8 V and 254.4 V	P
11.7	Shower units are operated for 2 min unless the water flow stops automatically. Other appliances are operated until steady conditions are established. (IEC 60335-2-84)	(see appended tables)	P
11.8	Temperature rises not exceeding values in table 3	(see appended tables)	P
	Sealing compound does not flow out		P
	Protective devices do not operate, except		P
	components in protective electronic circuits tested for the number of cycles specified in 24.1.4	No protective electronic circuits	N/A
	The temperature rises shall not exceed the values shown in Table 101 (IEC 60335-2-84)	(see appended table)	P
	The temperature of the water supplied by shower units shall not exceed 45°C	Max. 38.2 °C	P
13	LEAKAGE CURRENT AND ELECTRIC STRENGTH AT OPERATING TEMPERATURE		-
13.1	Leakage current not excessive and electric strength adequate		P
	Heating appliances operated at 1.15 times rated power input .....		N/A
	Motor-operated appliances and combined appliances supplied at 1.06 times rated voltage .....	254.4 V	P

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	Protective impedance and radio interference filters disconnected before carrying out the tests		N/A
13.2	Leakage current measured by means of the circuit described in figure 4 of IEC 60990		P
	Leakage current measurements	(see appended table)	P
	Water heaters having bare heating elements are tested with water having the resistivity stated in the instructions (IEC 60335-2-84)		N/A
	For water heaters of class I having bare heating elements, the leakage current is measured between a metal sieve positioned 10 mm from the spray head of the shower unit and the earthing terminal. The terminals of the heating element are connected through the selector switch to each pole of the supply in turn, as shown in Figure 101. (IEC 60335-2-84)		N/A
	The leakage current shall not exceed 0.25 mA (IEC 60335-2-84)		N/A
13.3	The appliance is disconnected from the supply		P
	Electric strength tests according to table 4	(see appended table)	P
	No breakdown during the tests		P
14	TRANSIENT OVERVOLTAGES		-
	Appliances withstand the transient overvoltages to which they may be subjected		N/A
	Clearances having a value less than specified in table 16 subjected to an impulse voltage test, the test voltage specified in table 6	(see appended table)	N/A
	No flashover during the test, unless of functional insulation		N/A
	In case of flashover of functional insulation, the appliance complies with clause 19 with the clearance short circuited		N/A
15	MOISTURE RESISTANCE		-
15.1	Enclosure provides the degree of moisture protection according to classification of the appliance		P
	Compliance checked as specified in 15.1.1, taking into account 15.1.2, followed by the electric strength test of 16.3		P
	No trace of water on insulation which can result in a reduction of clearances and creepage distances below values specified in clause 29		P
15.1.1	Appliances, other than IPX0, subjected to tests as specified in IEC 60529 .....	IPX4	P

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	Water valves in external hoses for connection of an appliance to the water mains tested as specified for IPX7 appliances		N/A
	It may be necessary to use the spray nozzle described in subclause 14.2.4(b) of IEC 60529 for testing the inside of the bowl. (IEC 60335-2-84)		P
15.1.2	Hand-held appliance turned continuously through the most unfavourable positions during the test		N/A
	Built-in appliances installed according to the instructions		N/A
	Appliances placed or used on the floor or table placed on a horizontal unperforated support		N/A
	Appliances normally fixed to a wall and appliances with pins for insertion into socket-outlets are mounted on a wooden board		N/A
	For IPX3 appliances, the base of wall mounted appliances is placed at the same level as the pivot axis of the oscillating tube		N/A
	For IPX4 appliances, the horizontal centre line of the appliance is aligned with the pivot axis of the oscillating tube		P
	However, for appliances normally used on the floor or table, the movement is limited to two times 90° for a period of 5 min, the support being placed at the level of the pivot axis of the oscillating tube		N/A
	Appliances normally fixed to a ceiling are mounted underneath a horizontal unperforated support, the pivot axis of the oscillating tube located at the level of the underside of the support		N/A
	For IPX4 appliances, the movement of the tube is limited to two times 90° from the vertical for a period of 5 min		P
	Wall-mounted appliances, take into account the distance to the floor stated in the instructions		N/A
	Appliances with type X attachment fitted with a flexible cord as described		N/A
	Detachable parts tested as specified		N/A
15.2	Spillage of liquid does not affect the electrical insulation		N/A
	Appliances with type X attachment fitted with a flexible cord as described		N/A
	Appliances incorporating an appliance inlet tested with or without an connector, whichever is most unfavourable		N/A



IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	Detachable parts removed		N/A
	Overfilling test with additional amount of water, over a period of 1 min (I)		N/A
	The appliance withstands the electric strength test of 16.3		N/A
	No trace of water on insulation that can result in a reduction of clearances and creepage distances below values specified in clause 29		N/A
15.3	Appliances proof against humid conditions		P
	Humidity test for 48 h in a humidity cabinet	93%RH, 30°C	P
	The appliance withstands the tests of clause 16		P
16	LEAKAGE CURRENT AND ELECTRIC STRENGTH		-
16.1	Leakage current not excessive and electric strength adequate		P
	Protective impedance disconnected from live parts before carrying out the tests		N/A
16.2	Single-phase appliances: test voltage 1.06 times rated voltage .....	254.4 V	P
	Three-phase appliances: test voltage 1.06 times rated voltage divided by $\sqrt{3}$ .....		N/A
	Leakage current measurements	(see appended table)	P
	Water heaters having bare heating elements are tested with water having the resistivity stated in the instructions (IEC 60335-2-84)	No such water heaters	N/A
16.3	Electric strength tests according to table 7	(see appended table)	P
	No breakdown during the tests		P
17	OVERLOAD PROTECTION OF TRANSFORMERS AND ASSOCIATED CIRCUITS		-
	No excessive temperatures in transformer or associated circuits in event of short-circuits likely to occur in normal use	(see appended table)	P
	Appliance supplied with 1.06 or 0.94 times rated voltage and the most unfavourable short-circuit or overload likely to occur in normal use applied .....	254.4 V	P
	Temperature rise of insulation of the conductors of safety extra-low voltage circuits not exceeding the relevant value specified in table 3 by more than 15 K		N/A
	Temperature of the winding not exceeding the value specified in table 8,		P
	however limits do not apply to fail-safe transformers complying with sub-clause 15.5 of IEC 61558-1		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
19	ABNORMAL OPERATION		-
19.1	The risk of fire or mechanical damage under abnormal or careless operation obviated		P
	Electronic circuits so designed and applied that a fault will not render the appliance unsafe		P
	Appliances incorporating contactors or relays subjected to the test of 19.14, being carried out before the tests of 19.11		P
	Appliances incorporating a automatic controls are also subjected to the test of 19.101 (IEC 60335-2-84)		P
19.2	Test of appliance with heating elements with restricted heat dissipation; test voltage (V): power input of 0.85 times rated power input	202 V (0.85 x 1670 W)	P
	Water heaters are tested with or without water, whichever is more unfavourable (IEC 60335-2-84)	With water	P
19.3	Test of 19.2 repeated; test voltage (V): power input of 1.24 times rated power input.....	269 V (1.24 x 1670 W)	P
19.4	Test conditions as in cl. 11, any control limiting the temperature during tests of cl. 11 short-circuited		P
19.5	Test of 19.4 repeated on Class 0I and I appliances with tubular sheathed or embedded heating elements. No short-circuiting, but one end of the element connected to the elements sheath		P
	The test repeated with reversed polarity and the other end of the heating element connected to the sheath		P
	The test is not carried out on appliances intended to be permanently connected to fixed wiring and on appliances where an all-pole disconnection occurs during the test of 19.4		N/A
19.6	Appliances with PTC heating elements tested at rated voltage, establishing steady conditions		N/A
	The working voltage of the PTC heating element is increased by 5% and the appliance is operated until steady conditions are re-established. The voltage is then increased in similar steps until 1.5 times working voltage or until the PTC heating element ruptures		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
19.7	Stalling test by locking the rotor if the locked rotor torque is smaller than the full load torque or locking moving parts of other appliances		P
	Locked rotor, motor capacitors open-circuited or short-circuited, if required	No motor capacitors	N/A
	Locked rotor, capacitors open-circuited one at a time		N/A
	Test repeated with capacitors short-circuited one at a time, if required		N/A
	Appliances with timer or programmer supplied with rated voltage for each of the tests, for a period equal to the maximum period allowed		P
	Other appliances supplied with rated voltage for a period as specified		P
	Winding temperatures not exceeding values specified in table 8	(see appended table)	P
19.8	Three-phase motors operated at rated voltage with one phase disconnected		N/A
19.10	Series motor operated at 1.3 times rated voltage for 1 min .....		N/A
	During the test, parts not being ejected from the appliance		N/A
19.11	Electronic circuits, compliance checked by evaluation of the fault conditions specified in 19.11.2 for all circuits or parts of circuits, unless they comply with the conditions specified in 19.11.1		P
	Appliances incorporating a protective electronic circuit subjected to the tests of 19.11.3 and 19.11.4		N/A
	Appliances having a switch with an off position obtained by electronic disconnection, or a switch placing the appliance in a stand-by mode, subjected to the tests of 19.11.4		P
	Appliances incorporating an electronic circuit that relies upon a programmable component to function correctly, subjected to the test of 19.11.4.8		N/A
19.11.1	Before applying the fault conditions a) to f) in 19.11.2, it is checked if circuits or parts of circuit meet both of the following conditions:		-
	- the electronic circuit is a low-power circuit, that is, the maximum power at low-power points does not exceed 15 W according to the tests specified		P
	- the protection against electric shock, fire hazard, mechanical hazard or dangerous malfunction in other parts of the appliance does not rely on the correct functioning of the electronic circuit		P

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
19.11.2	Fault conditions applied one at a time, the appliance operated under conditions specified in cl. 11, but supplied at rated voltage, the duration of the tests as specified:		
	a) short circuit of functional insulation if clearances or creepage distances are less than the values specified in 29		P
	b) open circuit at the terminals of any component		P
	c) short circuit of capacitors, unless they comply with IEC 60384-14		P
	d) short circuit of any two terminals of an electronic component, other than integrated circuits. This fault condition is not applied between the two circuits of an optocoupler		P
	e) failure of triacs in the diode mode		P
	f) failure of an integrated circuit		P
	g) failure of an electronic power switching device		P
19.11.3	If the appliance incorporates a protective electronic circuit which operates to ensure compliance with clause 19, the relevant test is repeated with a single fault simulated, as indicated in a) to f) of 19.11.2		N/A
	During and after each test the following is checked:		-
	- the temperature rise of the windings do not exceed the values specified in table 8		N/A
	- the appliance complies with the conditions specified in 19.13		N/A
	- any current flowing through protective impedance not exceeding the limits specified in 8.1.4		N/A
	If a conductor of a printed board becomes open-circuited, the appliance is considered to have withstood the particular test, provided all three of the following conditions are met:		-
	- the material of the printed circuit board withstands the burning test of annex E		N/A
	- any loosened conductor does not reduce the clearances or creepage distances between live parts and accessible metal parts below the values specified in cl. 29		N/A
	- the appliance withstands the tests of 19.11.2 with open-circuited conductor bridged		N/A
19.11.4	Appliances having a device with an off position obtained by electronic disconnection, or		P
	a device that can be placed in the stand-by mode,		P
	subjected to the tests of 19.11.4.1 to 19.11.4.7		P

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	Appliances incorporating a protective electronic circuit subjected to the tests of 19.11.4.1 to 19.11.4.7, except that		N/A
	appliances operated for 30 s or 5 min during the test of 19.7 are not subjected to the tests for electromagnetic phenomena.		N/A
19.11.4.1	The appliance is subjected to electrostatic discharges in accordance with IEC 61000-4-2, test level 4		P
19.11.4.2	The appliance is subjected to radiated fields in accordance with IEC 61000-4-3, test level 3		P
19.11.4.3	The appliance is subjected to fast transient bursts in accordance with IEC 61000-4-4, test level 3 or 4 as specified		P
19.11.4.4	The power supply terminals of the appliance subjected to voltage surges in accordance with IEC 61000-4-5, test level 3 or 4 as specified		P
	Earthed heating elements in class I appliances disconnected		P
19.11.4.5	The appliance is subjected to injected currents in accordance with IEC 61000-4-6, test level 3		P
19.11.4.6	The appliance is subjected to the Class 3 voltage dips and interruptions in accordance with IEC 61000-4-11		P
19.11.4.7	The appliance is subjected to mains signals in accordance with IEC 61000-4-13, test level class 2		P
19.11.4.8	The appliance is supplied at rated voltage and operated under normal operation. After 60s the power supply is reduces to a level such that the appliance ceases to respond or a programmable component cease to operate.		N/A
	The appliance continues to operate normally or requires a manual operation to restart		N/A
19.12	If the safety of the appliance for any of the fault conditions specified in 19.11.2 depends on the operation of a miniature fuse-link complying with IEC 60127, the test is repeated, measuring the current flowing through the fuse-link; measured current (A); rated current of the fuse-link (A) .....		P
19.13	During the tests the appliance does not emit flames, molten metal, poisonous or ignitable gas in hazardous amounts		P
	Temperature rises not exceeding the values shown in table 9	(see appended table)	P
	Compliance with cl. 8 not impaired		P

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	If the appliance can still be operated it complies with 20.2		P
	Insulation, other than of class III appliance, withstand the electric strength test of 16.3, the test voltage specified in table 4:		-
	- basic insulation .....	1000 V	P
	- supplementary insulation .....		N/A
	- reinforced insulation .....	3000 V	P
	After operation or interruption of a control, clearances and creepage distances across the functional insulation withstanding the electric strength test of 16.3. the test voltage being twice the working voltage		P
	The appliance does not undergo a dangerous malfunction, and		P
	no failure of protective electronic circuits, if the appliance is still operable		N/A
	Appliances tested with an electronic switch in the off position, or in the stand-by mode:		-
	- do not become operational, or		P
	- if they become operational, do not result in a dangerous malfunction during or after the tests of 19.11.4		N/A
	The temperature rises shall not exceed the values shown in Table 102 (IEC 60335-2-84)	(see appended table)	P
	The temperature of the water supplied by shower units shall not exceed 65°C (IEC 60335-2-84)	(see appended table)	P
19.14	Appliances operated under the conditions of Clause 11. Contactors or relays contacts operating under the conditions of clause 11 short-circuited		N/A
19.101	The appliance is supplied at rated voltage and operated under normal operation. Any fault condition which can be expected in normal use is applied one at the time (IEC 60335-2-84)		P

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
20	STABILITY AND MECHANICAL HAZARDS		-
20.1	Adequate stability	Fixed appliance	N/A
	Tilting test through an angle of 10° (appliance placed on an inclined plane/horizontal plane); appliance does not overturn		N/A
	Tilting test repeated on appliances with heating elements, angle of inclination increased to 15°		N/A
	Possible heating test in overturned position; temperature rise does not exceed values shown in table 9		N/A
20.2	Moving parts adequately arranged or enclosed as to provide protection against personal injury		P
	Protective enclosures, guards and similar parts are non-detachable		P
	Adequate mechanical strength and fixing of protective enclosures		P
	Self-resetting thermal cut-outs and overcurrent protective devices not causing a hazard, by unexpected reclosure		P
	Not possible to touch dangerous moving parts with test probe		P
21	MECHANICAL STRENGTH		-
21.1	Appliance has adequate mechanical strength and is constructed as to withstand rough handling		P
	Checked by applying blows to the appliance in accordance with test Ehb of IEC 60068-2-75, spring hammer test, impact energy 0,5 J		P
	If necessary, supplementary or reinforced insulation subjected to the electric strength test of 16.3		P
	If necessary, repetition of groups of three blows on a new sample		N/A
21.2	Accessible parts of solid insulation having strength to prevent penetration by sharp implements		P
	The insulation is tested as specified, unless		N/A
	the thickness of supplementary insulation is at least 1 mm and reinforced insulation is at least 2 mm		P
	Compliance is also checked by the tests of 21.101 and 21.102 (IEC 60335-2-84)		
21.101	The appliance is subjected to an evenly distributed force of 1500 N applied perpendicularly to the seat, the bowl cover being open, for 10 min (IEC 60335-2-84)		P

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	The test is repeated with the bowl closed (IEC 60335-2-84)		P
	A force of 250N is then applied to the front edge of the bowl cover or seat in a direction parallel to the hinges, the bowl cover or seat being slowly raised and lowered. The test is carried out 5 times. (IEC 60335-2-84)		P
	The bowl cover or seat is then raised and the force of 250 N is applied for 1 min to its front edge in a direction perpendicular to its plane. (IEC 60335-2-84)		P
	The appliance shall not be damaged to such an extent that compliance with 8.1, 15.1, 16.3 and 27.5 is impaired (IEC 60335-2-84)		P
21.102	The excrement tank is completely filled with water and the appliance placed in a room having a temperature of approximately -15°C. When the water is completely frozen, the appliance is allowed to warm up until the ice has melted. The test is carried out 3 times (IEC 60335-2-84)		N/A
	The appliance shall not be damaged to such an extent that compliance with 8.1, 15.1, 16.3 and 27.5 is impaired (IEC 60335-2-84)		N/A

22	CONSTRUCTION		-
22.1	Appliance marked with the first numeral of the IP system, relevant requirements of IEC 60529 are fulfilled		N/A
22.2	Stationary appliance: means to provide all-pole disconnection from the supply provided, the following means being available:		
	- a supply cord fitted with a plug		P
	- a switch complying with 24.3		N/A
	- a statement in the instruction sheet that a disconnection incorporated in the fixed wiring is to be provided		N/A
	- Class I appliances shall not incorporate an appliance an appliance inlet (IEC 60335-2-84)		N/A
	Single-pole switches and single-pole protective devices for the disconnection of heating elements in single-phase, permanently connected class 01 and class I appliances, connected to the phase conductor		N/A
22.3	Appliance provided with pins: no undue strain on socket-outlets		N/A
	Applied torque not exceeding 0.25 Nm		N/A



IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	Pull force of 50N to each pin after the appliance has been placed in the heating cabinet; when cooled to room temperature the pins are not displaced by more than 1mm		N/A
	Each pin subjected to a torque of 0.4Nm; the pins are not rotating unless rotating does not impair compliance with the standard		N/A
22.4	Appliance for heating liquids and appliance causing undue vibration not provided with pins for insertion into socket-outlets		P
22.5	No risk of electric shock when touching the pins of the plug, for appliances having a capacitor with rated capacitance exceeding 0,1 $\mu$ F, the appliance being disconnected from the supply at the instant of voltage peak	Measured: 0 V	P
22.6	Instead of coloured water, a solution composed of 0,6 ml of the rinsing agent per litre of distilled water is used IEC 60335-2-5, Annex AA		P
	Electrical insulation of Class II appliances not affected in case of a hose rupture or seal leak		P
22.7	Adequate safeguards against the risk of excessive pressure in appliances provided with steam-producing devices		P
22.8	Electrical connections not subject to pulling during cleaning of compartments to which access can be gained without the aid of a tool, and that are likely to be cleaned in normal use		P
22.9	Insulation, internal wiring, windings, commutators and slip rings not exposed to oil, grease or similar substances		P
	Adequate insulating properties of oil or grease to which insulation is exposed		N/A
22.10	Not possible to reset voltage-maintained non-self-resetting thermal cut-outs by the operation of an automatic switching device incorporated within the appliance		N/A
	Non-self resetting thermal motor protectors have a trip-free action, unless		N/A
	they are voltage maintained		N/A
	Location or protection of reset buttons of non-self-resetting controls is so that accidental resetting is unlikely		P
22.11	Reliable fixing of non-detachable parts that provide the necessary degree of protection against electric shock, moisture or contact with moving parts		P

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	Obvious locked position of snap-in devices used for fixing such parts		N/A
	No deterioration of the fixing properties of snap-in devices used in parts that are likely to be removed during installation or servicing		N/A
	Tests as described	Push and pull test conducted	P
22.12	Handles, knobs etc. fixed in a reliable manner		N/A
	Fixing in wrong position of handles, knobs etc. indicating position of switches or similar components not possible		N/A
	Axial force 15 N applied to parts, the shape being so that an axial pull is unlikely to be applied		N/A
	Axial force 30 N applied to parts, the shape being so that an axial pull is likely to be applied		N/A
22.13	Unlikely that handles, when gripped as in normal use, make the operators hand touch parts having a temperature rise exceeding the value specified for handles which are held for short periods only		N/A
22.14	No ragged or sharp edges creating a hazard for the user in normal use, or during user maintenance		P
	No exposed pointed ends of self tapping screws etc., liable to be touched by the user in normal use or during user maintenance		P
22.15	Storage hooks and the like for flexible cords smooth and well rounded	No storage hooks	N/A
22.16	Automatic cord reels cause no undue abrasion or damage to the sheath of the flexible cord, no breakage of conductors strands, no undue wear of contacts	No automatic cord reels	N/A
	Cord reel tested with 6000 operations, as specified		N/A
	Electric strength test of 16.3, voltage of 1000 V applied		N/A
22.17	Spacers not removable from the outside by hand or by means of a screwdriver or a spanner	No spacers	N/A
22.18	Current-carrying parts and other metal parts resistant to corrosion under normal conditions of use		P
22.19	Driving belts not used as electrical insulation	No driving belts	N/A
22.20	Direct contact between live parts and thermal insulation effectively prevented, unless material used is non-corrosive, non-hygroscopic and non-combustible	No such insulation	N/A
	Compliance is checked by inspection and, if necessary, by appropriate test		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
22.21	Wood, cotton, silk, ordinary paper and fibrous or hygroscopic material not used as insulation, unless impregnated		P
	This requirement does not apply to magnesium oxide and mineral ceramic fibres used for the electrical insulation of heating elements		N/A
22.22	Appliances not containing asbestos		P
22.23	Oils containing polychlorinated biphenyl (PCB) not used		P
22.24	Bare heating elements adequately supported	Dry heater	P
	In case of rupture, the heating conductor is unlikely to come in contact with accessible metal parts		P
	Appliances shall not incorporate bare heating elements located in excrement tanks. (IEC 60335-2-84)	No excrement tanks	N/A
	Compliance is checked by inspection (IEC 60335-2-84)		N/A
22.25	Sagging heating conductors cannot come into contact with accessible metal parts		N/A
22.26	The insulation between parts operating at safety extra-low voltage and other live parts complies with the requirements for double or reinforced insulation		N/A
22.27	Parts connected by protective impedance separated by double or reinforced insulation		N/A
22.28	Metal parts of Class II appliances conductively connected to gas pipes or in contact with water: separated from live parts by double or reinforced insulation	Class I	N/A
22.29	Class II appliances permanently connected to fixed wiring so constructed that the required degree of access to live parts is maintained after installation		N/A
22.30	Parts serving as supplementary or reinforced insulation fixed so that they cannot be removed without being seriously damaged, or		P
	so constructed that they cannot be replaced in an incorrect position, and so that if they are omitted, the appliance is rendered inoperable or manifestly incomplete		P
22.31	Clearances and creepage distances over supplementary and reinforced insulation not reduced below values specified in clause 29 as a result of wear		P

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	Clearances and creepage distances between live parts and accessible parts not reduced below values for supplementary insulation, if wires, screws etc. become loose		P
22.32	Supplementary and reinforced insulation designed or protected against deposition of dirt or dust		P
	Supplementary insulation of natural or synthetic rubber resistant to ageing, or arranged and dimensioned so that creepage distances are not reduced below values specified in 29.2		N/A
	Ceramic material not tightly sintered, similar material or beads alone not used as supplementary or reinforced insulation		N/A
	Oxygen bomb test at 70 °C for 96 h and 16 h at room temperature		N/A
	Insulating material in which heating conductors are embedded is considered to be basic insulation and not reinforced insulation		P
22.33	Liquids may be in direct contact with live parts of bare heating elements and may be heated using electrodes. (IEC 60335-2-84)		N/A
	For class II constructions, conductive liquids that are or may become accessible in normal use, not in direct contact with basic or reinforced insulation		P
	For class II constructions, conductive liquids which are in contact with live parts, not in direct contact with reinforced insulation		N/A
22.34	Shafts of operating knobs, handles, levers etc. not live, unless the shaft is not accessible when the part is removed		N/A
22.35	Handles, levers and knobs, held or actuated in normal use, not becoming live in the event of a failure of basic insulation		N/A
	Such parts being of metal, and their shafts or fixings are likely to become live in the event of a failure of basic insulation, are either adequately covered by insulation material or their accessible parts are separated from their shafts or fixings by supplementary insulation		N/A
	This requirement does not apply to handles, levers and knobs on stationary appliances other than those of electrical components, provided they are either reliably connected to an earthing terminal or earthing contact, or separated from live parts by earthed metal		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
22.36	Handles continuously held in the hand in normal use are so constructed that when gripped as in normal use, the operators hand is not likely to touch metal parts, unless they are separated from live parts by double or reinforced insulation		N/A
22.37	Capacitors in Class II appliances not connected to accessible metal parts, unless complying with 22.42		N/A
	Metal casings of capacitors in Class II appliances separated from accessible metal parts by supplementary insulation, unless complying with 22.42		N/A
22.38	Capacitors not connected between the contacts of a thermal cut-out		P
22.39	Lamp holders used only for the connection of lamps		N/A
22.40	Motor-operated appliances and combined appliances intended to be moved while in operation, or having accessible moving parts, fitted with a switch to control the motor. The actuating member of the switch being easily visible and accessible		N/A
	Unless the appliance can operate continuously, automatically or remotely without giving rise to a hazard, appliances for remote operation being fitted with a switch. The actuating member of the switch being easily visible and accessible.		N/A
22.41	No components, other than lamps, containing mercury		P
22.42	Protective impedance consisting of at least two separate components		N/A
	Values specified in 8.1.4 not exceeded if any one of the components are short-circuited or open-circuited		P
22.43	Appliances adjustable for different voltages, accidental changing of the setting of the voltage unlikely to occur		N/A
22.44	Appliances shall not have an enclosure that is shaped or decorated like a toy		P
22.45	When air is used as reinforced insulation, clearances not reduced below the values specified in 29.1.4 due to deformation as a result of an external force applied to the enclosure		P
22.46	Software used in protective electronic circuits is software class B or C .....		N/A
22.47	Appliances connected to the water mains withstand the water pressure expected in normal use	Rated: Max. 735,5 kPa Tested: 1,47 MPa Test duration: 5 min Result: No leakage	P

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	No leakage from any part, including any inlet water hose		P
22.48	Appliances connected to the water mains constructed to prevent backsiphonage of non-potable water		P
22.49	For remote operation, the duration of operation shall be set before the appliance can be started, unless		N/A
	the appliance switches off automatically or can operate continuously without hazard		N/A
22.50	Controls incorporated in the appliance take priority over controls actuated by remote operation		N/A
22.51	A control on the appliance being manually adjusted to the setting for remote operation before the appliance can be operated in this mode		N/A
	There is a visual indication showing that the appliance is adjusted for remote operation		N/A
	Manual setting and visual indication not necessary on appliances that can operate as follows, without giving rise to a hazard:		-
	- operate continuously,		N/A
	- operate automatically, or		N/A
	- be operated remotely		N/A
22.52	Socket-outlets on appliances accessible to the user in accordance with the socket-outlet system used in the country in which the appliance is sold		N/A
22.101	Toilets shall be fixed appliances (IEC 60335-2-84)		N/A
	Compliance is checked by inspection (IEC 60335-2-84)		N/A
22.102	Metal parts in contact with the skin and which support the body in normal use shall not be earthed (IEC 60335-2-84)		P
	Compliance is checked by inspection (IEC 60335-2-84)		P
22.103	Live parts are protected from exposure to excrement (IEC 60335-2-84)		N/A
	Compliance is checked by inspection (IEC 60335-2-84)		N/A
	And if rubber seals are used , compliance is checked by the following test (IEC 60335-2-84):		N/A
	The seal is immersed for 24h in mineral oil having a temperature of 100 °C ± 2 °C.After the test the volume of the seal shall not have increased by more than 50%.(IEC 60335-2-84)		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
22.104	Vacuum toilets cannot be flushed unless the bowl cover is closed. (IEC 60335-2-84)		N/A
	Compliance is checked by inspection (IEC 60335-2-84)		N/A

23	INTERNAL WIRING		-
23.1	Wireways smooth and free from sharp edges		P
	Wires protected against contact with burrs, cooling fins etc.		P
	Wire holes in metal well rounded or provided with bushings		N/A
	Wiring effectively prevented from coming into contact with moving parts		P
23.2	Beads etc. on live wires cannot change their position, and are not resting on sharp edges or corners		N/A
	Beads inside flexible metal conduits contained within an insulating sleeve		N/A
23.3	Electrical connections and internal conductors movable relatively to each other not exposed to undue stress		P
	Flexible metallic tubes not causing damage to insulation of conductors		N/A
	Open-coil springs not used		N/A
	Adequate insulating lining provided inside a coiled spring, the turns of which touch one another		N/A
	No damage after 10 000 flexings for conductors flexed during normal use or 100 flexings for conductors flexed during user maintenance		N/A
	Heated seats: the number of flexing is 50 000 (IEC 60335-2-84)		P
	Electric strength test, 1000 V between live parts and accessible metal parts		P
23.4	Bare internal wiring sufficiently rigid and fixed	No bare internal wiring	N/A
23.5	The insulation of internal wiring withstanding the electrical stress likely to occur in normal use		P
	No breakdown when a voltage of 2000 V is applied for 15 min between the conductor and metal foil wrapped around the insulation		P
	Internal wiring supplying parts in the excrement tank at safety extra-low voltage shall not be lighter than ordinary polyvinyl chloride sheathed cord (cord designation 60227 IEC 53) (IEC 60335-2-84)		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
23.6	Sleeving used as supplementary insulation on internal wiring retained in position by positive means		P
23.7	The colour combination green/yellow used only for earthing conductors		P
23.8	Aluminium wires not used for internal wiring		P
23.9	No lead-tin soldering of stranded conductors where they are subject to contact pressure, unless		P
	clamping means so constructed that there is no risk of bad contact due to cold flow of the solder		N/A
23.10	The insulation and sheath of internal wiring, incorporated in external hoses for the connection of an appliance to the water mains, at least equivalent to that of light polyvinyl chloride sheathed flexible cord (60227 IEC 52)		N/A

24	COMPONENTS		-
24.1	Components comply with safety requirements in relevant IEC standards		P
	List of components	(see appended table)	P
	Components not tested and found to comply with relevant IEC standard for the number of cycles specified are tested in accordance with 24.1.1 to 24.1.9		P
	Components not tested and found to comply with relevant IEC standard, components not marked or not used in accordance with its marking, tested under the conditions occurring in the appliance		P
	Lampholders and starterholders not being tested and found to comply with the relevant IEC standard, tested as a part of the appliance and additionally according to the gauging and interchangeability requirements of the relevant IEC standard		N/A
24.1.1	Capacitors likely to be permanently subjected to the supply voltage and used for radio interference suppression or for voltage dividing, complying with IEC 60384-14, or		P
	tested according to annex F		N/A
24.1.2	Safety isolating transformers complying with IEC 61558-2-6, or		N/A
	tested according to annex G		P
24.1.3	Switches complying with IEC 61058-1, the number of cycles of operation being at least 10 000, or		N/A
	tested according to annex H		N/A



IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	If the switch operates a relay or contactor, the complete switching system is subjected to the test		N/A
24.1.4	Automatic controls complying with IEC 60730-1 with relevant part 2. The number of cycles of operation being:		
	- thermostats: 10 000		N/A
	- temperature limiters: 1 000		N/A
	- self-resetting thermal cut-outs: 300		N/A
	- voltage maintained non-self-resetting thermal cut-outs: 1000		N/A
	- other non-self-resetting thermal cut-outs: 30		N/A
	- timers: 3 000		N/A
	- energy regulators: 10 000		N/A
	Thermal motor protectors are tested in combination with their motor under the conditions specified in Annex D		N/A
	For water valves containing live parts and that are incorporated in external hoses for connection of an appliance to the water mains, the degree of protection declared for subclause 6.5.2 of IEC 60730-2-8 is IPX7		N/A
24.1.5	Appliance couplers complying with IEC 60320-1		N/A
	However, appliances classified higher than IPX0, the appliance couplers complying with IEC 60320-2-3		N/A
	Not applicable to conditions as specified (IEC 60335-2-9)	No interconnection couplers	N/A
24.1.6	Small lamp holders similar to E10 lampholders complying with IEC 60238, the requirements for E10 lampholders being applicable		N/A
24.1.7	If the remote operation of the appliance is via a telecommunication network, the relevant standard for the telecommunication interface circuitry in the appliance is IEC 62151		N/A
24.1.8	The relevant standard for thermal links is IEC 60691. Thermal links not complying with IEC 60691 are considered to be an intentionally weak part for the purposes of Clause 19		P
24.1.9	Relays, other than motor starting relays, tested as part of the appliance		N/A
	They are also tested in accordance with Clause 17 of IEC 60730-1, the number of operations in 24.1.4 selected according to the relay function in the appliance.....:		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
24.2	No switches or automatic controls in flexible cords		P
	No devices causing the protective device in the fixed wiring to operate in the event of a fault in the appliance		P
	No thermal cut-outs that can be reset by soldering		P
24.3	Switches intended for all-pole disconnection of stationary appliances are directly connected to the supply terminals and having a contact separation in all poles, providing full disconnection under overvoltage category III conditions		N/A
24.4	Plugs and socket-outlets for extra-low voltage circuits and heating elements, not interchangeable with plugs and socket-outlets listed in IEC 60083 or IEC 60906-1 or with connectors and appliance inlets complying with the standard sheets of IEC 60320-1		N/A
24.5	Capacitors in auxiliary windings of motors marked with their rated voltage and capacitance and used accordingly		N/A
	Voltage across capacitors in series with a motor winding does not exceed 1,1 times rated voltage, when the appliance is supplied at 1,1 times rated voltage under minimum load		N/A
24.6	Working voltage of motors connected to the supply mains and having basic insulation that is inadequate for the rated voltage of the appliance, not exceeding 42V		N/A
	In addition, the motors are complying with the requirements of Annex I		N/A
24.7	Hose-sets for connection of appliances to the water mains, complying with IEC 61770 and supplied with the appliance		P
24.101	Thermal cut-out incorporated in appliances for compliance with 19.4 or 19.101 shall not be self-resetting (IEC 60335-2-84)		P
	Compliance is checked by inspection (IEC 60335-2-84)		P

25	SUPPLY CONNECTION AND EXTERNAL FLEXIBLE CORDS		-
25.1	Appliance not intended for permanent connection to fixed wiring, means for connection to the supply:		-
	- supply cord fitted with a plug		P
	- an appliance inlet having at least the same degree of protection against moisture as required for the appliance		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	- pins for insertion into socket-outlets		N/A
25.2	Appliance not provided with more than one means of connection to the supply mains		P
	Stationary appliance for multiple supply may be provided with more than one means of connection, provided electric strength test of 1250 V for 1 min between each means of connection causes no breakdown		N/A
25.3	Connection of supply conductors for appliance intended to be permanently connected to fixed wiring possible after the appliance has been fixed to its support		N/A
	Appliance provided with a set of terminals for the connection of cables or fixed wiring, cross-sectional areas specified in 26.6		N/A
	Appliance provided with a set of terminals allowing the connection of a flexible cord		N/A
	Appliance provided with a set of supply leads accommodated in a suitable compartment		N/A
	Appliance provided with a set of terminals and cable entries, conduit entries, knock-outs or glands, allowing connection of appropriate type of cable or conduit		N/A
	Appliances incorporating water heaters having bare heating elements shall only be provided with means for connection to fixed wiring. (IEC 60335-2-84)		N/A
25.4	Cable and conduit entries, rated current of appliance not exceeding 16 A, dimension according to table 10		N/A
	Introduction of conduit or cable does not reduce clearances or creepage distances below values specified in 29		N/A
25.5	Method for assemble supply cord with the appliance:		-
	- type X attachment		N/A
	- type Y attachment		P
	- type Z attachment, if allowed in part 2		N/A
	Type X attachment, other than those with a specially prepared cord, not used for flat twin tinsel cords		N/A
25.6	Plugs fitted with only one flexible cord		P
25.7	Supply cords being one of the following types:		-
	- rubber sheathed (at least 60245 IEC 53)		N/A
	- polychloroprene sheathed (at least 60245 IEC 57)		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	- cross-linked polyvinyl chloride sheathed (at least 60245 IEC 87)		N/A
	Polyvinyl chloride sheathed: Not used if they are likely to touch metal parts having a temperature rise exceeding 75K during the test of Clause 11.		-
	- light polyvinyl chloride sheathed cord (at least 60227 IEC 52), appliances not exceeding 3 kg		N/A
	- ordinary polyvinyl chloride sheathed cord (at least 60227 IEC 53), other appliances	H05VV-F; 1.0 mm <sup>2</sup>	P
	Heat resistant polyvinyl chloride sheathed: Not used for type X attachment other than specially prepared cords.		-
	- Heat-resistant light polyvinyl chloride sheathed cord (at least 60227 IEC 56), appliances not exceeding 3 kg		N/A
	- heat-resistant polyvinyl chloride sheathed cord (60227 IEC 57), other appliances		N/A
25.8	Nominal cross-sectional area of supply cords according to table 11; rated current (A); cross-sectional area (mm <sup>2</sup> ).....:	7.3 A; 1.0 mm <sup>2</sup>	P
25.9	Supply cord not in contact with sharp points or edges		P
25.10	Green/yellow core for earthing purposes in Class I appliance		P
25.11	Conductors of supply cords not consolidated by lead-tin soldering where they are subject to contact pressure, unless		P
	clamping means so constructed that there is no risk of bad contacts due to cold flow of the solder		N/A
25.12	Moulding the cord to part of the enclosure does not damage the insulation of the supply cord		N/A
25.13	Inlet opening so shaped as to prevent damage to the supply cord		P
	Unless the enclosure at the inlet opening is of insulation material, a non-detachable lining or bushing complying with 29.3 for supplementary insulation provided		P
	If unshathed supply cord, a similar additional bushing or lining is required, unless		N/A
	the appliance is class 0		N/A
25.14	Supply cords adequately protected against excessive flexing		N/A
	Flexing test:		⊥
	- applied force (N) .....		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	- number of flexings .....		N/A
	The test does not result in:		-
	- short circuit between the conductors		N/A
	- breakage of more than 10% of the strands of any conductor		N/A
	- separation of the conductor from its terminal		N/A
	- loosening of any cord guard		N/A
	- damage, within the meaning of the standard, to the cord or the cord guard		N/A
	- broken strands piercing the insulation and becoming accessible		N/A
25.15	Conductors of the supply cord relieved from strain, twisting and abrasion by use of cord anchorage		P
	The cord cannot be pushed into the appliance to such an extent that the cord or internal parts of the appliance can be damaged		P
	Pull and torque test of supply cord, values shown in table 10: pull (N); torque (not on automatic cord reel) (Nm) .....	100 N; 0.35 Nm	P
	Max. 2 mm displacement of the cord, and conductors not moved more than 1 mm in the terminals		P
	Creepage distances and clearances not reduced below values specified in 29.1		P
25.16	Cord anchorages for type X attachments constructed and located so that:		-
	- replacement of the cord is easily possible		N/A
	- it is clear how the relief from strain and the prevention of twisting are obtained		N/A
	- they are suitable for different types of cord		N/A
	- cord cannot touch the clamping screws of cord anchorage if these screws are accessible, unless separated from accessible metal parts by supplementary insulation		N/A
	- the cord is not clamped by a metal screw which bears directly on the cord		N/A
	- at least one part of the cord anchorage securely fixed to the appliance, unless part of a specially prepared cord		N/A
	- screws which have to be operated when replacing the cord do not fix any other component, if applicable		N/A
	- if labyrinths can be bypassed the test of 25.15 is nevertheless withstood		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	- for Class 0, 0I and I appliances: they are of insulating material or are provided with an insulating lining, unless a failure of the insulation of the cord does not make accessible metal parts live		N/A
	- for Class II appliances: they are of insulating material, or if of metal, they are insulated from accessible metal parts by supplementary insulation		N/A
25.17	Adequate cord anchorages for type Y and Z attachment	Type Y attachment	P
25.18	Cord anchorages only accessible with the aid of a tool, or		P
	so constructed that the cord can only be fitted with the aid of a tool		N/A
25.19	Type X attachment, glands not used as cord anchorage in portable appliances		N/A
	Tying the cord into a knot or tying the cord with string not used		N/A
25.20	Conductors of the supply cord for type Y and Z attachment adequately additionally insulated		P
25.21	Space for supply cord for type X attachment or for connection of fixed wiring constructed to permit checking of conductors with respect to correct positioning and connection before fitting any cover, no risk of damage to the conductors when fitting the cover, no contact with accessible metal parts if a conductor becomes loose, etc.		N/A
	For portable appliances, the uninsulated end of a conductor prevented from any contact with accessible metal parts, unless the end of the cord is such that the conductors are unlikely to slip free		N/A
25.22	Appliance inlet:		-
	- live parts not accessible during insertion or removal		N/A
	- connector can be inserted without difficulty		N/A
	- the appliance is not supported by the connector		N/A
	- is not for cold conditions if temp. rise of external metal parts exceeds 75 K, unless the supply cord is not likely to touch such metal parts		N/A
25.23	Interconnection cords comply with the requirements for the supply cord, except as specified		N/A
	If necessary, electric strength test of 16.3		N/A
25.24	Interconnection cords not detachable without the aid of a tool if compliance with the standard is impaired when they are disconnected		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
25.25	Dimensions of pins compatible with the dimensions of the relevant socket-outlet. Dimensions of pins and engagement face in accordance with the relevant plug in IEC 60083		N/A
26	TERMINALS FOR EXTERNAL CONDUCTORS		-
26.1	Appliances provided with terminals or equally effective devices for connection of external conductors		N/A
	Terminals only accessible after removal of a non-detachable cover		N/A
	However, earthing terminals may be accessible if a tool is required to make the connections and means are provided to clamp the wire independently from its connection		N/A
26.2	Appliances with type X attachment and appliances for connection to fixed wiring provided with terminals in which connections are made by means of screws, nuts or similar devices, unless the connections are soldered		N/A
	Screws and nuts serve only to clamp supply conductors, except		N/A
	internal conductors, if so arranged that they are unlikely to be displaced when fitting the supply conductors		N/A
	If soldered connections used, the conductor so positioned or fixed that reliance is not placed on soldering alone		N/A
	Soldering alone used, barriers provided, clearances and creepage distances satisfactory if the conductor becomes free at the soldered joint		N/A
26.3	Terminals for type X attachment and for connection to fixed wiring so constructed that the conductor is clamped between metal surfaces with sufficient contact pressure and without damaging the conductor		N/A
	Terminals for type X attachment and those for connection to fixed wiring so fixed that when tightening or loosening the clamping means:		-
	- the terminal does not loosen		N/A
	- internal wiring is not subjected to stress		N/A
	- clearances and creepage distances are not reduced below the values in 29		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	Compliance checked by inspection and by the test of subclause 9.6 of IEC 60999-1, the torque applied being equal to two-thirds of the torque specified. Nominal diameter of thread (mm); screw category; torque (Nm):		N/A
26.4	Terminals for type X attachment, except those with a specially prepared cord, and those for connection to fixed wiring, no special preparation of conductors required, and so constructed or placed that conductors prevented from slipping out		N/A
26.5	Terminals for type X attachment so located or shielded that if a wire of a stranded conductor escapes, no risk of accidental connection to other parts that result in a hazard		N/A
	Stranded conductor test, 8 mm insulation removed		N/A
	No contact between live parts and accessible metal parts and, for class II constructions, between live parts and metal parts separated from accessible metal parts by supplementary insulation only		N/A
26.6	Terminals for type X attachment and for connection to fixed wiring suitable for connection of conductors with required cross-sectional area according to table 13; rated current (A); nominal cross-sectional area (mm <sup>2</sup> ) .....		N/A
	Terminals only suitable for a specially prepared cord		N/A
26.7	Terminals for type X attachment accessible after removal of a cover or part of the enclosure		N/A
26.8	Terminals for the connection to fixed wiring, including the earthing terminal, located close to each other		N/A
26.9	Terminals of the pillar type constructed and located as specified		N/A
26.10	Terminals with screw clamping and screwless terminals not used for flat twin tinsel cords, unless conductors ends fitted with a device suitable for screw terminals		N/A
	Pull test of 5 N to the connection		N/A
26.11	For type Y and Z attachment: soldered, welded, crimped and similar connections may be used		P
	For Class II appliances: the conductor so positioned or fixed that reliance is not placed on soldering, welding or crimping alone		N/A
	For Class II appliances: soldering, welding or crimping alone used, barriers provided, clearances and creepage distances satisfactory if the conductor becomes free		N/A



IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
27	PROVISION FOR EARTHING		-
27.1	Accessible metal parts of Class 0I and I appliances, permanently and reliably connected to an earthing terminal or contact of the appliance inlet		P
	Earthing terminals not connected to neutral terminal		P
	Class 0, II and III appliance have no provision for earthing		N/A
	Safety extra-low voltage circuits not earthed, unless protective extra-low voltage circuits		N/A
	For class I appliances incorporating water heaters having bare elements, the water shall enter and leave through metal pipes that are permanently and reliably connected to the earthing terminal or flow over metal parts that are similarly earthed. (IEC 60335-2-84)	No such water heaters	N/A
27.2	Clamping means adequately secured against accidental loosening		P
	Terminals used for the connection of external equipotential bonding conductors allow connection of conductors of 2.5 to 6 mm <sup>2</sup> , and		N/A
	do not provide earthing continuity between different parts of the appliance		N/A
	Conductors cannot be loosened without the aid of a tool		P
27.3	For detachable parts that are plugged into another part of the appliance, and having an earth connection, the earth connection made before and separated after current-carrying connections when removing the part		N/A
	For appliances with supply cord, current-carrying conductors become taut before earthing conductor, if the cord slips out of the cord anchorage		P
27.4	No risk of corrosion resulting from contact between metal of earthing terminal and other metal		P
	Adequate resistance to corrosion of coated or uncoated parts providing earthing continuity, other than parts of a metal frame or enclosure		P
	Parts of steel providing earthing continuity provided at the essential areas with an electroplated coating, thickness at least 5 µm		N/A
	Adequate protection against rusting of parts of coated or uncoated steel, only intended to provide or transmit contact pressure		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	In case of aluminium alloys precautions taken to avoid risk of corrosion		N/A
27.5	Low resistance of connection between earthing terminal and earthed metal parts		P
	This requirement does not apply to connections providing earthing continuity in the protective extra-low voltage circuit, provided that clearances of basic insulation are based on the rated voltage of the appliance		N/A
	Resistance not exceeding 0,1 $\Omega$ at the specified low-resistance test	0.017 $\Omega$	P
27.6	The printed conductors of printed circuit boards shall not be used to provide earthing continuity in hand-held appliances.		N/A
	They may be used to provide earthing continuity in other appliances if at least two tracks are used with independent soldering points and the appliance complies with 27.5 for each circuit		N/A
28	SCREWS AND CONNECTIONS		-
28.1	Fixings, electrical connections and connections providing earthing continuity withstand mechanical stresses		P
	Screws not of soft metal liable to creep, such as zinc or aluminium		P
	Diameter of screws of insulating material min. 3 mm		N/A
	Screws of insulating material not used for any electrical connection or connections providing earthing continuity		N/A
	Screws used for electrical connections or connections providing earthing continuity screw into metal		P
	Screws not of insulating material if their replacement by a metal screw can impair supplementary or reinforced insulation		N/A
	Type X attachment, screws to be removed for replacement of supply cord or for user maintenance, not of insulating material if their replacement by a metal screw can impair basic insulation		N/A
	For screws and nuts; test as specified	(see appended table)	P
28.2	Electrical connections and connections providing earthing continuity constructed so that contact pressure not transmitted through insulating material liable to shrink or distort, unless shrinkage or distortion compensated		P

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	This requirement does not apply to electrical connections in circuits carrying a current not exceeding 0.5A		N/A
28.3	Space-threaded (sheet metal) screws only used for electrical connections if they clamp the parts together		N/A
	Thread-cutting (self-tapping) screws and thread rolling screws only used for electrical connections if they generate a full form standard machine screw thread		N/A
	Thread-cutting (self-tapping) screws not used if they are likely to be operated by the user or installer		N/A
	Thread-cutting, thread rolling and space threaded screws may be used in connections providing earthing continuity provided it is not necessary to disturb the connection:		-
	- in normal use,		N/A
	- during user maintenance,		N/A
	- when replacing a supply cord having a type X attachment, or		N/A
	- during installation		N/A
	At least two screws being used for each connection providing earthing continuity, unless		N/A
	the screw forms a thread having a length of at least half the diameter of the screw		N/A
	Thread-cutting and space-threaded screws may be used in connections providing earthing continuity, provided unnecessary to disturb the connection and at least two screws are used for each connection		N/A
28.4	Screws and nuts that make mechanical connection secured against loosening if they also make electrical connections or connections providing earthing continuity		P
	Rivets for electrical connections or connections providing earthing continuity secured against loosening if subjected to torsion		N/A

29	CLEARANCES, CREEPAGE DISTANCES AND SOLID INSULATION		-
	Clearances, creepage distances and solid insulation withstand electrical stress		P
	For coatings used on printed circuits boards to protect the microenvironment (Type 1) or to provide basic insulation (Type 2), annex J applies..... :		N/A
	The microenvironment is pollution degree 1 under Type 1 coating		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	No clearance or creepage distance requirements under Type 2 coating		N/A
29.1	Clearances not less than the values specified in table 16, taking into account the rated impulse voltage for the overvoltage categories of table 15, unless		P
	for basic insulation and functional insulation they comply with the impulse voltage test of clause 14		N/A
	However, if the construction is affected by wear, distortion, movement of the parts or during assembly, the clearances for rated impulse voltages of 1500V and above are increased by 0,5 mm and the impulse voltage test is not applicable		N/A
	Impulse voltage test not applicable:		-
	- when the microenvironment is pollution degree 3		N/A
	- for basic insulation of class 0 and class 01 appliances		N/A
	Appliances are in overvoltage category II		P
	Clearances less than specified in table 16 not allowed for basic insulation of class 0 and class 0I appliances,		N/A
	or if pollution degree 3 is applicable		N/A
	Compliance is checked by inspection and measurements as specified		P
29.1.1	Clearances of basic insulation withstand the overvoltages, taking into account the rated impulse voltage		P
	Clearance at the terminals of tubular sheathed heating elements may be reduced to 1mm if the microenvironment is pollution degree 1		N/A
	Lacquered conductors of windings considered to be bare conductors		P
29.1.2	Clearances of supplementary insulation not less than those specified for basic insulation in table 16		P
29.1.3	Clearances of reinforced insulation not less than those specified for basic insulation in table 16, but using the next higher step for rated impulse voltage		P
29.1.4	For functional insulation, the values of table 16 are applicable, unless		P
	the appliance complies with clause 19 with the functional insulation short-circuited		N/A
	Lacquered conductors of windings considered to be bare conductors		P

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	However, clearances at crossover points are not measured		P
	Clearance between surfaces of PTC heating elements may be reduced to 1mm		N/A
29.1.5	Appliances having higher working voltage than rated voltage, the voltage used for determining clearances from table 16 is the sum of the rated impulse voltage and the difference between the peak value of the working voltage and the peak value of the rated voltage		N/A
	If the secondary winding of a step-down transformer is earthed, or if there is an earthed screen between the primary and secondary windings, clearances of basic insulation on the secondary side not less than those specified in table 16, but using the next lower step for rated impulse voltage		N/A
	Circuits supplied with a voltage lower than rated voltage, clearances of functional insulation based on the working voltage used as the rated voltage in table 15		N/A
29.2	Creepage distances not less than those appropriate for the working voltage, taking into account the material group and the pollution degree		P
	Pollution degree 2 applies, unless		P
	precautions taken to protect the insulation; pollution degree 1		N/A
	insulation subjected to conductive pollution; pollution degree 3		N/A
	The microenvironment is pollution degree 3 (IEC 60335-2-84),		N/A
	Unless the insulation is enclosed or located so that it is unlikely to be exposed to pollution during normal use of the appliance.( IEC 60335-2-84),		N/A
29.2.1	Creepage distances of basic insulation not less than specified in table 17		P
	For pollution degree 1, creepage distance not less than the minimum specified for the clearance in table 16, if the clearance has been checked according to the test of clause 14		N/A
29.2.2	Creepage distances of supplementary insulation at least as specified for basic insulation in table 17		P
29.2.3	Creepage distances of reinforced insulation at least double as specified for basic insulation in table 17		P
29.2.4	Creepage distances of functional insulation not less than specified in table 18		P

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	Creepage distances may be reduced if the appliance complies with clause 19 with the functional insulation short-circuited		N/A
29.3	Supplementary and reinforced insulation having adequate thickness, or a sufficient number of layers, to withstand the electrical stresses		P
	Compliance checked by:		-
	- measurement, in accordance with 29.3.1, or		P
	- an electric strength test in accordance with 29.3.2, or		N/A
	- an assessment of the thermal quality of the material combined with an electric strength test, in accordance with 29.3.3		N/A
29.3.1	Supplementary insulation having a thickness of at least 1 mm		P
	Reinforced insulation having a thickness of at least 2 mm		P
29.3.2	Each layer of material withstand the electric strength test of 16.3 for supplementary insulation		N/A
	Supplementary insulation consisting of at least 2 layers		N/A
	Reinforced insulation consisting of at least 3 layers		N/A
29.3.3	The insulation is subjected to the dry heat test Bb of IEC 60068-2-2, followed by		N/A
	the electric strength test of 16.3		N/A
	If the temperature rise during the tests of Clause 19 does not exceed the value specified in Table 3, the test of IEC 60068-2-2 is not carried out		N/A

30	RESISTANCE TO HEAT AND FIRE		-
30.1	External parts of non-metallic material,		P
	parts supporting live parts, and		P
	thermoplastic material providing supplementary or reinforced insulation,		P
	sufficiently resistant to heat		P
	Ball-pressure test according to IEC 60695-10-2		P
	External parts: at 40 °C plus the maximum temperature rise determined during the test of clause 11, or at 75 °C, whichever is the higher; temperature (°C).....:	(see appended table)	P

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	Parts supporting live parts: at 40°C plus the maximum temperature rise determined during the test of clause 11, or at 125°C, whichever is the higher; temperature (°C) .....	(see appended table)	P
	Parts of thermoplastic material providing supplementary or reinforced insulation, 25°C plus the maximum temperature rise determined during clause 19, if higher; temperature (°C).....		N/A
30.2	Parts of non-metallic material adequately resistant to ignition and spread of fire		P
	This requirement does not apply to decorative trims, knobs and other parts unlikely to be ignited or to propagate flames that originate inside the appliance		N/A
	Compliance checked by the test of 30.2.1. In addition:		-
	- attended appliances, 30.2.2 applies		N/A
	- unattended appliances, 30.2.3 applies		P
	Appliances for remote operation, 30.2.3 applies		N/A
	Base material of printed circuit board, 30.2.4 applies		P
30.2.1	Glow-wire test of IEC 60695-2-11 at 550 °C, unless	(see appended table)	P
	the material is classified at least HB40 according to IEC 60695-11-10		N/A
	Parts for which the glow-wire test cannot be carried out meet the requirements in ISO9772 for category HBF material		N/A
30.2.2	Not applicable ( IEC 60335-2-84)		P
30.2.3	Appliances operated while unattended, tested as specified in 30.2.3.1 and 30.2.3.2		P
	Tests not applicable to conditions as specified		N/A
30.2.3.1	Parts of insulating material supporting connections carrying a current exceeding 0.2A during normal operation, and		P
	parts of non-metallic material within a distance of 3mm,		P
	subjected to the glow-wire test of IEC 60695-2-11 with a test severity of 850°C	(see appended table)	P
	Glow-wire test not carried out on parts of material classified as having a glow-wire flammability index of at least 850°C according to IEC 60695-2-12		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	Glow-wire test not carried out on small parts that comply with the needle-flame test of Annex E or on small parts of material classified as V-0 or V-1 according to IEC 60695-11-10		N/A
	Test as specified for an interposed shielding material		N/A
	The specified glow-wire flammability index is not applicable to water heaters having bare heating elements. (IEC 60335-2-84)		N/A
30.2.3.2	Parts of non-metallic material supporting current-carrying connections, and		P
	parts of non-metallic material within a distance of 3mm,		P
	subjected to glow-wire test of IEC 60695-2-11		P
	Test not carried out on material having a glow-wire ignition temperature according to IEC 60695-2-13 of at least:		N/A
	-775°C, for connections carrying a current exceeding 0,2A during normal operation		N/A
	-675°C, for other connections		N/A
	When the glow-wire test of IEC 60695-2-11 is carried out, the temperatures are:		-
	-750°C, for connections carrying a current exceeding 0,2A during normal operation	(see appended table)	P
	-650°C, for other connections		N/A
	Parts that during the test produce a flame persisting longer than 2 s, tested as specified		N/A
	If a flame persists longer than 2 s during the test, parts above the connection, as specified, subjected to the needle-flame test of annex E, unless		P
	the material is classified as V-0 or V-1 according to IEC 60695-11-10		P
	For water heaters having bare heating elements, the glow-wire test is carried out as specified for other connections. (IEC 60335-2-84)		N/A
30.2.4	Base material of printed circuit boards subjected to needle-flame test of annex E		P
	Test not applicable to conditions as specified		N/A
30.101	The bowl shall not incorporate combustible material (IEC 60335-2-84)		N/A
	Compliance is checked by subjecting non-metallic material to the needle-flame test of Annex E. (IEC 60335-2-84)		N/A



IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	The test is not carried out if the material is classified as V-0 according to IEC 60695-11-10, provided that the test sample was not thicker than the relevant part. (IEC 60335-2-84)		N/A
31	RESISTANCE TO RUSTING		-
	Relevant ferrous parts adequately protected against rusting		N/A
	Compliance is checked by the salt mist test of IEC 60068-2-52, severity 2 being applicable. (IEC 60335-2-84)		N/A
32	RADIATION, TOXICITY AND SIMILAR HAZARDS		-
	Appliance shall not emit harmful radiation, present a toxic or similar hazard due to their operation in normal use		N/A
	Relevant tests specified in part 2, if necessary		N/A
A	ANNEX A (INFORMATIVE) ROUTINE TESTS		-
	Description of routine tests to be carried out by the manufacturer		P
B	ANNEX B (NORMATIVE) APPLIANCES POWERED BY RECHARGEABLE BATTERIES		-
	The following modifications to this standard are applicable for appliances powered by batteries that are recharged in the appliance		N/A
	This annex does not apply to battery chargers		N/A
3.1.9	Appliance operated under the following conditions:		-
	-the appliance, supplied by its fully charged battery, operated as specified in relevant part 2		N/A
	-the battery is charged, the battery being initially discharged to such an extent that the appliance cannot operate		N/A
	-if possible, the appliance is supplied from the supply mains through its battery charger, the battery being initially discharged to such an extent that the appliance cannot operate. The appliance is operated as specified in relevant part 2		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	If the appliance incorporates inductive coupling between two parts that are detachable from each other, the appliance is supplied from the supply mains with the detachable part removed		N/A
3.6.2	Part to be removed in order to discard the battery is not considered to be detachable		N/A
5.101	Appliances supplied from the supply mains tested as specified for motor-operated appliances		N/A
7.1	Battery compartment for batteries intended to be replaced by the user, marked with battery voltage and polarity of the terminals		N/A
7.12	The instructions for appliances incorporating batteries intended to be replaced by the user includes required information		N/A
	Details about how to remove batteries containing materials hazardous to the environment given		N/A
7.15	Markings placed on the part of the appliance connected to the supply mains		N/A
8.2	Appliances having batteries that according to the instruction may be replaced by the user need only have basic insulation between live parts and the inner surface of the battery compartment		N/A
	If the appliance can be operated without batteries, double or reinforced insulation required		N/A
11.7	The battery is charged for the period described		N/A
19.1	Appliances subjected to tests of 19.101, 19.102 and 19.103		N/A
19.101	Appliances supplied at rated voltage for 168 h, the battery being continually charged		N/A
19.102	Short-circuiting of the terminals of the battery, being fully charged, for appliances having batteries that can be removed without the aid of a tool		N/A
19.103	Appliances having batteries replaceable by the user supplied at rated voltage under normal operation with the battery removed or in any position allowed by the construction		N/A
21.101	Appliances having pins for insertion into socket-outlets have adequate mechanical strength, checked according to procedure 2 of IEC 68-2-32		N/A
	Part of the appliance incorporating the pins subjected to the free fall test, procedure 2, of IEC 60068-2-32, the number of falls being:		
	- 100, the mass of part does not exceed 250 g		N/A
	- 50, the mass of part exceeds 250 g		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	After the test, the requirements of 8.1, 15.1.1, 16.3 and clause 29 are met		N/A
22.3	Appliances having pins for insertion into socket-outlets tested as fully assembled as possible		N/A
25.13	An additional lining or bushing not required for interconnection cords operating at safety extra-low voltage		N/A
30.2	For parts of the appliance connected to the supply mains during the charging period, 30.2.3 applies		N/A
	For other parts, 30.2.2 applies		N/A
C	ANNEX C (NORMATIVE) AGEING TEST ON MOTORS		-
	Tests, as described, carried out when doubt with regard to the temperature classification of the insulation of a motor winding		N/A
D	ANNEX D (NORMATIVE) THERMAL MOTOR PROTECTORS		-
	Applicable to appliances having motors that incorporate thermal motor protectors		N/A
E	ANNEX E (NORMATIVE) NEEDLE-FLAME TEST		-
	Needle-flame test carried out in accordance with IEC 60695-11-5, with the following modifications:		P
7	Severities		-
	The duration of application of the test flame is 30 s ± 1 s		P
9	Test procedure		-
9.1	The specimen so arranged that the flame can be applied to a vertical or horizontal edge as shown in the examples of figure 1		P
9.2	The first paragraph does not apply		P
	If possible, the flame is applied at least 10 mm from a corner		P
9.3	The test is carried out on one specimen		P
	If the specimen does not withstand the test, the test may be repeated on two additional specimens, both withstanding the test		N/A
11	Evaluation of test results		-

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	The duration of burning not exceeding 30 s		P
	However, for printed circuit boards, the duration of burning not exceeding 15 s		P

F	ANNEX F (NORMATIVE) CAPACITORS		-
	Capacitors likely to be permanently subjected to the supply voltage, and used for radio interference suppression or voltage dividing, comply with the following clauses of IEC 60384-14, with the following modifications:		N/A
1.5	Terminology		-
1.5.3	Class X capacitors tested according to subclass X2		N/A
1.5.4	This subclause is applicable		N/A
1.6	Marking		-
	Items a) and b) are applicable		N/A
3.4	Approval testing		-
3.4.3.2	Table II is applicable as described		N/A
4.1	Visual examination and check of dimensions		-
	This subclause is applicable		N/A
4.2	Electrical tests		-
4.2.1	This subclause is applicable		N/A
4.2.5	This subclause is applicable		N/A
4.2.5.2	Only table IX is applicable		N/A
	Values for test A apply		N/A
	However, for capacitors in heating appliances the values for test B or C apply		N/A
4.12	Damp heat, steady state		-
	This subclause is applicable		N/A
	Only insulation resistance and voltage proof are checked		N/A
4.13	Impulse voltage		-
	This subclause is applicable		N/A
4.14	Endurance		-
	Subclauses 4.14.1, 4.14.3, 4.14.4 and 4.14.7 applicable		N/A
4.14.7	Only insulation resistance and voltage proof are checked		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	Visual examination, no visible damage		N/A
4.17	Passive flammability test		-
	This subclause is applicable		N/A
4.18	Active flammability test		-
	This subclause is applicable		N/A
G	ANNEX G (NORMATIVE) SAFETY ISOLATING TRANSFORMERS		-
	The following modifications to this standard are applicable for safety isolating transformers:		P
7	Marking and instructions		-
7.1	Transformers for specific use marked with:		-
	-name, trademark or identification mark of the manufacturer or responsible vendor		P
	-model or type reference		P
17	Overload protection of transformers and associated circuits		-
	Fail-safe transformers comply with subclause 15.5 of IEC 61558-1		N/A
22	Construction		-
	Subclauses 19.1 and 19.1.2 of IEC 61558-2-6 are applicable		P
29	Clearances, creepage distances and solid insulation		-
29.1, 29.2 and 29.3	The distances specified in items 2a, 2c and 3 in table 13 of IEC 61558-1 apply		P
H	ANNEX H (NORMATIVE) SWITCHES		-
	Switches comply with the following clauses of IEC 61058-1, as modified:		-
	-The tests of IEC 61058-1 carried out under the conditions occurring in the appliance		N/A
	-Before being tested, switches are operated 20 times without load		N/A
8	Marking and documentation		-
	Switches are not required to be marked		N/A
	However, switches that can be tested separately from the appliance marked with the manufacturer's name or trade mark and the type reference		N/A
13	Mechanism		-
	The tests may be carried out on a separate sample		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
15	Insulation resistance and dielectric strength		
15.1	Not applicable		N/A
15.2	Not applicable		N/A
15.3	Applicable for full disconnection and micro-disconnection		N/A
17	Endurance		-
	Compliance is checked on three separate appliances or switches		N/A
	For 17.2.4.4, the number of cycles is 10 000, unless otherwise specified in 24.1.3 of the relevant part 2 of IEC 60335		N/A
	Switches for operation under no load and which can be operated only by a tool and switches operated by hand that are interlocked so that they cannot be operated under load, are not subjected to the tests		N/A
	Subclauses 17.2.2 and 17.2.5.2 not applicable		N/A
	The ambient temperature during the test is that occurring in the appliance during the test of Clause 11 in IEC 60335-1		N/A
	Temperature rise of the terminals not more than 30 K above the temperature rise measured in clause 11 of IEC 60335-1		N/A
20	Clearances, creepage distances, solid insulation and coatings of rigid printed board assemblies		-
	This clause is applicable to clearances and creepage distances for functional insulation, across full disconnection and micro-disconnection, as stated in table 24		N/A

I	ANNEX I (NORMATIVE) MOTORS HAVING BASIC INSULATION THAT IS INADEQUATE FOR THE RATED VOLTAGE OF THE APPLIANCE		-
	The following modifications to this standard are applicable for motors having basic insulation that is inadequate for the rated voltage of the appliance:		N/A
8	Protection against access to live parts		-
8.1	Metal parts of the motor are considered to be bare live parts		N/A
11	Heating		-
11.3	Temperature rise of the body of the motor is determined instead of the temperature rise of the windings		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
11.8	Temperature rise of the body of the motor, where in contact with insulating material, not exceeding values in table 3 for the relevant insulating material		N/A
16	Leakage current and electric strength		-
16.3	Insulation between live parts of the motor and its other metal parts not subjected to the test		N/A
19	Abnormal operation		-
19.1	The tests of 19.7 to 19.9 not carried out		N/A
19.101	Appliance operated at rated voltage with each of the following fault conditions:		-
	- short circuit of the terminals of the motor, including any capacitor incorporated in the motor circuit		N/A
	- short circuit of each diode of the rectifier		N/A
	- open circuit of the supply to the motor		N/A
	- open circuit of any parallel resistor, the motor being in operation		N/A
	Only one fault simulated at a time, the tests carried out consecutively		N/A
22	Construction		-
22.101	For class I appliances incorporating a motor supplied by a rectifier circuit, the d.c. circuit being insulated from accessible parts of the appliance by double or reinforced insulation		N/A
	Compliance checked by the tests specified for double and reinforced insulation		N/A
J	ANNEX J (NORMATIVE) COATED PRINTED CIRCUIT BOARDS		-
	Testing of protective coatings of printed circuit boards carried out in accordance with IEC 60664-3 with the following modifications:		N/A
5.7	Conditioning of the test specimens		-
	When production samples are used, three samples of the printed circuit board are tested		N/A
5.7.1	Cold		-
	The test is carried out at -25°C		N/A
5.7.3	Rapid change of temperature		-
	Severity 1 is specified		N/A
5.9	Additional tests		-
	This subclause is not applicable		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict

K	ANNEX K (NORMATIVE) OVERVOLTAGE CATEGORIES		-
	The information on overvoltage categories is extracted from IEC 60664-1	II	P
	Overvoltage category is a numeral defining a transient overvoltage condition		P
	Equipment of overvoltage category IV is for use at the origin of the installation		N/A
	Equipment of overvoltage category III is equipment in fixed installations and for cases where the reliability and the availability of the equipment is subject to special requirements		N/A
	Equipment of overvoltage category II is energy consuming equipment to be supplied from the fixed installation		P
	If such equipment is subjected to special requirements with regard to reliability and availability, overvoltage category III applies		N/A
	Equipment of overvoltage category I is equipment for connection to circuits in which measures are taken to limit transient overvoltages to an appropriate low level		N/A
L	ANNEX L (INFORMATIVE) GUIDANCE FOR THE MEASUREMENT OF CLEARANCES AND CREEPAGE DISTANCES		-
	Sequences for the determination of clearances and creepage distances		P

M	ANNEX M (NORMATIVE) POLLUTION DEGREE		-
	The information on pollution degrees is extracted from IEC 60664-1		P
	Pollution		-
	The microenvironment determines the effect of pollution on the insulation, taking into account the microenvironment		P
	Means may be provided to reduce pollution at the insulation by effective enclosures or similar		P
	Minimum clearances specified where pollution may be present in the microenvironment		P
	Degrees of pollution in the microenvironment		-



IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
	For evaluating creepage distances, the following degrees of pollution in the microenvironment are established:		-
	- pollution degree 1: no pollution or only dry, non-conductive pollution occurs. The pollution has no influence		N/A
	- pollution degree 2: only non-conductive pollution occurs, except that occasionally a temporary conductivity caused by condensation is to be expected		P
	- pollution degree 3: conductive pollution occurs or dry non-conductive pollution occurs that becomes conductive due to condensation that is to be expected		N/A
	- pollution degree 4: the pollution generates persistent conductivity caused by conductive dust or by rain or snow		N/A
N	ANNEX N (NORMATIVE) PROOF TRACKING TEST		-
	The proof tracking test is carried out in accordance with IEC 60112 with the following modifications:		N/A
7	Test apparatus		-
7.3	Test solutions		-
	Test solution A is used		N/A
10	Determination of proof tracking index (PTI)		-
10.1	Procedure		-
	The proof voltage is 100V, 250V, 175V, 400V or 600V.....:		N/A
	The last paragraph of Clause 3 applies		N/A
	The test is carried out on five specimens		N/A
	In case of doubt, additional test with proof voltage reduced by 25V, the number of drops increased to 100		N/A
10.2	Report		-
	The report stating if the PTI value was based on a test using 100 drops with a test voltage of (PTI-25) V		N/A
O	ANNEX O (INFORMATIVE) SELECTION AND SEQUENCE OF THE TESTS OF CLAUSE 30		-
	Description of tests for determination of resistance to heat and fire		P

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict

P	ANNEX P (INFORMATIVE) GUIDANCE FOR THE APPLICATION OF THIS STANDARD TO APPLIANCES USED IN WARM DAMP EQUABLE CLIMATES		-
	Modifications applicable for class 0 and 01 appliances having a rated voltage exceeding 150V, intended to be used in countries having a warm damp equable climate and that are marked WDaE		-
	Modifications may also be applied to class 1 appliances having a rated voltage exceeding 150V, intended to be used in countries having a warm damp equable climate and that are marked WdaE, if liable to be connected to a supply mains that excludes the protective earthing conductor		-
5	General conditions for the tests		-
5.7	The ambient temperature for the tests of Clauses 11 and 13 is $40^{+3}/_0$		N/A
7	Marking and instructions		-
7.1	The appliance marked with the letters WDaE		N/A
7.12	The instructions state that the appliance is to be supplied through a RCD having a rated residual operating current not exceeding 30 mA		N/A
	The instructions state that the appliance is considered to be suitable for use in countries having a warm damp equable climate, but may also be used in other countries		N/A
11	Heating		-
11.8	The values of Table 3 are reduced by 15 K		N/A
13	Leakage current and electric strength at operating temperature		
13.2	The leakage current for class I appliances not exceeding 0,5 mA		N/A
15	Moisture resistance		-
15.3	The value of t is 37 °C		N/A
16	Leakage current and electric strength		-
16.2	The leakage current for class I appliances not exceeding 0,5 mA		N/A
19	Abnormal operation		-
19.13	The leakage current test of 16.2 is applied in addition to the electric strength test of 16.3		N/A

Q	ANNEX Q (INFORMATIVE) SEQUENCE OF TESTS FOR THE EVALUATION OF ELECTRONIC CIRCUITS		-
	Description of tests for appliances incorporating electronic circuits		P

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
R	ANNEX R (NORMATIVE) SOFTWARE EVALUATION		-
	Software evaluated in accordance with the following clauses of Annex H of IEC 60730-1, as modified		-
H.2	Definitions		-
	Only definitions H.2.16 to H.2.20 applicable		N/A
H.7	Information		-
	Only footnotes 12) to 18) of Table 7.2, as modified, applicable		N/A
H.11.12	Controls using software		--
	All the subclauses of H.11.12, as modified, except H.11.12.6 and H.11.12.6.1, applicable		N/A
H.11.12.7	Delete text		N/A
H.11.12.7.1	For appliances using software class C having a single channel with self-test and monitoring structure, the manufacturer provides the measures necessary to address the fault/errors in safety related segments and data		N/A
H.11.12.8	Software fault/error detection occurs before compliance with 19.13 of IEC 60335-1 is impaired		N/A
H.11.12.8.1	Replace text		N/A
H.11.12.13	Software and safety related hardware under its control initializes and terminates before compliance with 19.13 of IEC 60335-1 is impaired		N/A

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict

10.1	TABLE: Power input deviation					P
Input deviation of/at:	P rated (W)	P measured (W)	dP	Required dP	Remark	
230 V / 50 Hz	1670	1633	-2.22 %	+ 5 %, - 10 %	1)	
230 V / 60 Hz	1670	1640	-1.79 %	+ 5 %, - 10 %	1)	
230 V / 50 Hz	-	266	-	-	2)	
230 V / 60 Hz	-	268	-	-	2)	
Note 1. Operating mode 1) "Enema" Mode + Water pressure: Max + Seat Temp: Max + Water Temp: Max + Massage: ON + Pulse: ON + Nozzle Position: FR max 2) "Dry" mode" with Dry temp: Max + Seat Temp: Max Note 2. tested sample: model <b>DIB-2000</b> Note 3. Arithmetic mean value is applied.						

10.1	TABLE: Power input deviation					P
Input deviation of/at:	P rated (W)	P measured (W)	dP	Required dP	Remark	
230 V / 50 Hz	1670	1600	- 4.19 %	+ 5 %, - 10 %	1)	
230 V / 60 Hz	1670	1602	- 4.07 %	+ 5 %, - 10 %	1)	
230 V / 50 Hz	-	184	-	-	2)	
230 V / 60 Hz	-	185	-	-	2)	
Note 1. Operating mode 1) "Power Wash" Mode + Water pressure: Max + Seat Temp: Max + Water Temp: Max + Massage : ON + Pulse: ON + Nozzle Position: FR max 2) "Dry" mode" with Dry temp: Max + Seat Temp: Max Note 2. tested sample: model <b>HDB-2500R</b> Note 3. Arithmetic mean value is applied.						

10.2	TABLE: Current deviation					N/A
Current deviation of/at:	I rated (A)	I measured (A)	dI	Required dI	Remark	

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict

11.8	TABLE: Heating test, thermocouples		P	
	Test voltage (V) .....	206.8 V 50 Hz / 254.4 V 50 Hz	—	
	Ambient (°C).....	24.0 °C / 24.7 °C	—	
Thermocouple locations		dT (K)		Max. dT (K)
		206.8 V 50 Hz	254.4 V 50 Hz	
AC cord sheath (inside)		3.5	3.0	35
AC connector body		6.6	6.3	For Cl. 30.1
EMI coil (L1)		6.7	6.6	65
X-capacitor body (C2)		7.6	8.0	50
Heater wire near heating element		8.7	8.2	50
Thermostat body (Heater part)		9.2	9.2	-
Water tank body		13.9	15.2	For Cl. 30.1
Solenoid body		14.9	21.2	-
Surface of insulation tube (near thermal fuse)		9.1	9.1	150 °C
Ground terminal near PCB of Q1		10.0	9.7	60
Nozzle motor body		5.7	5.1	-
Flow select motor body		7.7	7.4	-
Water pump motor body		16.6	16.4	-
Deodorant motor body		-0.6	-0.8	-
Linefilter coil		9.1	9.2	65
Transformer coil (SMPS)		27.0	28.4	65
Electric capacitor body		16.5	17.2	80 (T=105 °C)
Moulding surface (Main IC)		8.3	8.8	-
PCB supporter		3.8	4.2	For Cl. 30.1
Warm water		11.9	13.5	45 °C
Surface of seat body		15.4	15.5	25
Control button part (side)		0.9	1.1	For Cl. 30.1
Top of enclosure		3.2	3.6	For Cl. 30.1
Inside of enclosure		4.3	4.6	For Cl. 30.1
Dry fan motor body		4.4	4.8	-
Note: 1. Operating mode: wash 1) "Enema" Mode + Water pressure: Max + Seat Temp: Max + Water Temp: Max + Massage: ON + Pulse: ON + Nozzle Position: FR max				
Note 2. tested sample: model <b>DIB-2000</b>				

11.8	TABLE: Heating test, thermocouples		P	
	Test voltage (V) .....	206.8 V 50 Hz / 254.4 V 50 Hz	—	
	Ambient (°C).....	23.3 °C / 23.4 °C	—	
Thermocouple locations		dT (K)		Max. dT (K)
		206.8 V 50 Hz	254.4 V 50 Hz	

IEC 60335-2-84				
Clause	Requirement + Test	Result - Remark	Verdict	
	AC cord sheath (inside)	1.3	0.8	35
	AC connector body	2.0	1.4	For Cl. 30.1
	EMI coil (L1)	2.0	1.2	65
	X-capacitor body (C2)	3.5	2.8	50
	Heater wire near heating element	2.7	0.6	50
	Thermostat body (Heater part)	2.0	0.4	-
	Water tank body	3.3	0.7	For Cl. 30.1
	Solenoid body	1.4	1.2	-
	Surface of insulation tube (near thermal fuse)	2.3	0.6	150 °C
	Ground terminal near PCB of Q1	2.5	-0.2	60
	Nozzle motor body	1.9	0.4	-
	Flow select motor body	1.6	1.0	-
	Water pump motor body	2.8	1.4	-
	Deodorant motor body	0.9	-1.9	-
	Linefilter coil	5.9	4.2	65
	Transformer coil (SMPS)	15.6	14.4	65
	Electric capacitor body	9.0	7.7	80 (T=105 °C)
	Moulding surface (Main IC)	4.6	3.0	-
	PCB supporter	2.4	1.7	For Cl. 30.1
	Warm air (Dry mode)	21.9	27.2	40
	Surface of seat body	15.1	15.0	25
	Control button part (side)	0.3	-0.1	For Cl. 30.1
	Top of enclosure	1.7	1.2	For Cl. 30.1
	Inside of enclosure	3.0	1.4	For Cl. 30.1
	Dry fan motor body	2.5	2.0	-
Note 1. Operating mode: dry 1) "Dry" mode" with Dry temp: Max + Seat Temp: Max				
Note 2. tested sample: model <b>DIB-2000</b>				

11.8	TABLE: Heating test, resistance method					P
	Test voltage (V) .....			206.8 V / 254.4 V		—
	Ambient, t <sub>1</sub> (°C) .....			23.6 °C		—
	Ambient, t <sub>2</sub> (°C) .....			1) 24.0 °C / 2) 24.7 °C		—
	Temperature rise of winding	R <sub>1</sub> (Ω)	R <sub>2</sub> (Ω)	dT (K)	Max. dT (K)	Insulation class
	1) Solenoid valve (206.8 V)	5.18	5.61	21.03	75	Class 105
	2) Solenoid valve (254.4 V)	5.18	5.90	34.77	75	Class 105
Note: 1. Operating mode 1) "Enema" Mode + Water pressure: Max + Seat Temp: Max + Water Temp: Max + Massage: ON + Pulse: ON + Nozzle Position: FR max						
Note 2. tested sample: model <b>DIB-2000</b>						

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict
11.8	TABLE: Heating test, thermocouples		P
	Test voltage (V) .....	206.8 V 50 Hz / 254.4 V 50 Hz	—
	Ambient (°C).....	24.4 °C / 24.0 °C	—
Thermocouple locations	dT (K)		Max. dT (K)
	206.8 V 50 Hz	254.4 V 50 Hz	
AC cord sheath (inside)	4.4	3.1	35
AC connector body	11.2	3.2	For Cl. 30.1
EMI coil (L1)	9.5	5.2	65
X-capacitor body (C2)	11.2	7.2	50
Heater wire near heating element	7.4	6.3	50
Thermostat body (Heater part)	9.5	9.1	-
Water tank body	11.5	11.6	For Cl. 30.1
Solenoid body	19.6	28.0	-
Surface of insulation tube (near thermal fuse)	8.9	8.1	150 °C
Ground terminal near PCB of Q1	10.1	10.2	60
Nozzle motor body	7.1	5.1	-
Flow select motor body	9.2	7.8	-
Air pump motor body	9.2	7.7	-
Deodorant motor body	-3.6	-0.6	-
Linefilter coil	11.4	6.4	65
Transformer coil (SMPS)	19.5	14.5	65
Electric capacitor body	15.1	10.0	80 (T=105 °C)
Moulding surface (Main IC)	11.4	7.1	-
PCB supporter	7.4	3.1	For Cl. 30.1
Warm water	11.7	12.9	45 °C
Surface of seat body	12.8	13.7	25
Control button part (side)	1.9	1.5	For Cl. 30.1
Top of enclosure	5.3	13.8	For Cl. 30.1
Inside of enclosure	4.3	2.0	For Cl. 30.1
Dry fan motor body	7.5	3.1	-
Note 1. Operating mode: wash 1) "Power Wash" Mode + Water pressure: Max + Seat Temp: Max + Water Temp: Max + Massage : ON + Pulse: ON + Nozzle Position: FR max			
Note 2. tested sample: model <b>HDB-2500R</b>			

11.8	TABLE: Heating test, thermocouples		P
	Test voltage (V) .....	206.8 V 50 Hz / 254.4 V 50 Hz	—
	Ambient (°C).....	23.3 °C / 23.4 °C	—
Thermocouple locations	dT (K)		Max. dT (K)
	206.8 V 50 Hz	254.4 V 50 Hz	
AC cord sheath (inside)	0.2	1.8	35

IEC 60335-2-84				
Clause	Requirement + Test	Result - Remark	Verdict	
	AC connector body	2.8	3.3	For Cl. 30.1
	EMI coil (L1)	4.5	4.3	65
	X-capacitor body (C2)	6.8	6.1	50
	Heater wire near heating element	8.9	10.8	50
	Thermostat body (Heater part)	7.1	7.6	-
	Water tank body	9.6	10.4	For Cl. 30.1
	Solenoid body	8.8	11.1	-
	Surface of insulation tube (near thermal fuse)	7.6	8.4	150 °C
	Ground terminal near PCB of Q1	8.6	9.7	60
	Nozzle motor body	6.6	6.0	-
	Flow select motor body	8.9	7.2	-
	Air pump motor body	7.3	7.2	-
	Deodorant motor body	2.7	-2.6	-
	Linefilter coil	10.1	10.3	65
	Transformer coil (SMPS)	21.3	20.4	65
	Electric capacitor body	15.0	14.0	80 (T=105 °C)
	Moulding surface (Main IC)	9.6	8.8	-
	PCB supporter	4.1	4.7	For Cl. 30.1
	Warm air (Dry mode)	19.9	26.2	40
	Surface of seat body	15.5	12.7	25
	Control button part (side)	1.3	1.3	For Cl. 30.1
	Top of enclosure	2.1	2.9	For Cl. 30.1
	Inside of enclosure	5.6	7.3	For Cl. 30.1
	Dry fan motor body	4.5	6.2	-
Note 1. Operating mode: dry 1) "Dry" mode" with Dry temp: Max + Seat Temp: Max				
Note 2. tested sample: model <b>HDB-2500R</b>				

11.8	TABLE: Heating test, resistance method					P
	Test voltage (V) .....	206.8 V / 254.4 V			—	
	Ambient, t <sub>1</sub> (°C) .....	1), 2) 23.6 °C / 3), 4) 24.6 °C			—	
	Ambient, t <sub>2</sub> (°C) .....	1), 3) 24.4 °C / 2), 4) 24.0 °C			—	
	Temperature rise of winding	R <sub>1</sub> (Ω)	R <sub>2</sub> (Ω)	dT (K)	Max. dT (K)	Insulation class
	1) Solenoid valve (206.8 V)	5.18	5.71	25.60	75	Class 105
	2) Solenoid valve (254.4 V)	5.18	5.82	31.49	75	Class 105
	3) Air Pump Motor coil (206.8 V)	23.97	25.80	18.90	75	Class 105
	4) Air Pump Motor coil (254.4 V)	23.97	25.91	20.49	75	Class 105
Note 1. Operating mode 1) "Power Wash" Mode + Water pressure: Max + Seat Temp: Max + Water Temp: Max + Massage : ON + Pulse: ON + Nozzle Position: FR max						
Note 2. tested sample: model <b>HDB -2500R</b>						



IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict

13.2	TABLE: Leakage current		P
	Heating appliances: 1.15 x rated input.....:	-	—
	Motor-operated and combined appliances: 1.06 x rated voltage.....:	254.4 V	—
Leakage current between		I (mA)	Max. allowed I (mA)
L/N and Water		0.08	0.25
L/N and Non-metallic enclosure		0.01	0.25

13.3	TABLE: Electric strength		P
Test voltage applied between:		Voltage (V)	Breakdown (Yes/No)
Basic insulation		1000	No
Reinforced insulation		3000	No

14	TABLE: Transient overvoltages					N/A
Clearance between:	CI (mm)	Required CI (mm)	Rated impulse voltage (V)	Impulse test voltage (V)	Flashover (Yes/No)	

16.2	TABLE: Leakage current		P
	Single phase appliances: 1.06 x rated voltage.....:	254.4V	—
	Three phase appliances 1.06 x rated voltage divided by $\sqrt{3}$ .....:	-	—
Leakage current between		I (mA)	Max. allowed I (mA)
L/N and Water		0.08	0.25
L/N and Non-metallic enclosure		0.01	0.25

16.3	TABLE: Electric strength		P
Test voltage applied between:		Voltage (V)	Breakdown (Yes/No)
Basic insulation		1250	No
Reinforced insulation		3000	No

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict

17	TABLE: Overload protection, temperature rise		P
Temperature rise of part/at:	dT (K)	Max. dT (K)	
Transformer coil	84.9	175	

19.7	TABLE: Abnormal operation, locked rotor/moving parts					P
	Test voltage (V) .....	240 V				—
	Ambient, t <sub>1</sub> (°C) .....	1) 23.3 °C, 2) 24.9 °C 3) 25.0 °C, 4) 24.9 °C 5) 24.5 °C				—
	Ambient, t <sub>2</sub> (°C) .....	1) 23.5 °C, 2) 25.0 °C 3) 25.0 °C, 4) 24.9 °C 5) 24.5 °C				—
Temperature of winding	R <sub>1</sub> (Ω)	R <sub>2</sub> (Ω)	dT (K)	T (°C)	Max. T (°C)	
1) Solenoid valve	-	-	-	76.5	150	
2) Dry fan motor	-	-	-	53.7	150	
3) Deodorization fan motor	-	-	-	110.0	200	
4) Water pump	-	-	-	140.0	200	
5) Air Pump motor	-	-	-	70.4	150	

19.9	TABLE: Abnormal operation, running overload					N/A
	Test voltage (V) .....					—
	Ambient, t <sub>1</sub> (°C) .....					—
	Ambient, t <sub>2</sub> (°C) .....					—
Temperature of winding	R <sub>1</sub> (Ω)	R <sub>2</sub> (Ω)	dT (K)	T (°C)	Max. T (°C)	

19.13	TABLE: Abnormal operation, temperature rises		P
Thermocouple locations	dT (K)	Max. dT (K)	
Power cord sheath (at Cl. 19.3)	2.9	150	
Enclosure, inside (at Cl. 19.4)	7.6	For Cl. 30.1	
Seat (at Cl. 19.3)	19.1	55	
Warm air (at Cl. 19.2)	10.6	65	
Water (at Cl. 19.3)	36.9 °C	65 °C	

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict

24.1	TABLE: Components					P
Object / part No.	Manufacturer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity	
Power plug	KOREA KDK	KKP-4819R KKP-4819D	AC 250 V; 16 A	IEC 60884-1	VDE	
Power cord	KOREA KDK	H05VV-F	3 G X 1.0 mm <sup>2</sup>	60227 IEC53	VDE	
Material of main enclosure (Top& Bottom)	LG CHEMICAL (G UANGZHOU) ENG INEERING PLAST ICS CO LTD	SG-175	HB	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)	
Film Label	Mianyang Longhua Film Co Ltd.	PC1870A(a)-ECO	VTM-0	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)	
Solenoid valve	Jeil Electronics Co	JIE-497	220 V, Class 105 (A)	EN 60335-1 EN 60335-2-84	Tested in appliance	
Water pump motor	NSM Electronics	GGMN-1200	12 V dc, 0.8 A< Class 105 (A)	EN 60335-1 EN 60335-2-84	Tested in appliance	
Air pump motor (for DIB-2500R)	Daehan Nakagawa	DN-AP2	DC 12 V, Class 105 (A)	EN 60335-1 EN 60335-2-84	Tested in appliance	
Nozzle Stepping Motor	Leili Electrical Equipment Co., Ltd.	35BY412S-114G	12 V dc, 400 Ma, Class 105 (A)	EN 60335-1 EN 60335-2-84	Tested in appliance	
Deodorization fan motor	Zhongshan Hengshan Plastic Products Co., Ltd.	FS75302L	12 V dc, 0.1 A, Class 105 (A)	EN 60335-1 EN 60335-2-84	Tested in appliance	
Air Duct Beneath Deodorization DC Fan	BASF Co Ltd.	GP-35	HB	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)	
Water valve (stepping) Motor	Leili Electrical Equipment Co., Ltd.	24BYJ46-144W	12 V dc, 50 Ohms, Class 105 (A)	EN 60335-1 EN 60335-2-84	Tested in appliance	
<b>Seat Assembly</b>						
Toilet Seat Cover	LG CHEMICAL (GUANGZHOU) ENGINEERING PLASTICS CO LTD	SG-175	HB	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)	
Toilet Seat (Top/Base)	LG CHEMICAL (GUANGZHOU) ENGINEERING PLASTICS CO LTD	SG-175	HB	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)	
Seat heater	Dong Kook Electronics Co., Ltd.	CSB-1000	AC 220 V, 55 W	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)	
Heating Wire	Canaan Electronic & Precision Co Ltd.	1137	300 V, 105 °C, 55 W	EN 60335-1 EN 60335-2-84	Tested in appliance	
Thermal Cutoff	Dong Yang Electronics Co Ltd	DF77S	250 V, 10 A, 77 °C	EN 60691	TUV VDE	
Alt.)	Sung Woo Industrial Co.	SW-105T	AC 250 V, 10/15 A, 77 °C	EN 60691	VDE	

IEC 60335-2-84					
Clause	Requirement + Test			Result - Remark	Verdict
Insulation Tubing for Thermal Cutoff	Samhwa KDK Co.Ltd.	ACE TUBE HF	600 V, 125 °C	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)
Thermal Sensor (Thermistor)	James Tech	N3JC-K41A-DW1	1074 kohm ± 5 %at 25 °C	EN 60335-1 EN 60335-2-84	Tested in appliance
Seat Sensor	AD semiconductor	ADM-HxxxLW-xxW	5.5 V dc, 0.1 W	EN 60335-1 EN 60335-2-84	Tested in appliance
<b>Liquid Storage Chamber Assembly</b>					
Liquid Storage Chamber (Top/Base)	LG Chemical Ltd.	GP-2150	HB	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)
Non-self-resetting thermal cut-out	Pacific controls Co., Ltd.	PTS-13 or PTS 13H	250/125 V, 10/15 A, 60Hz, 55 °C	EN 60730-1 EN 60730-2-9	TUV
Alt)	Pacific controls Co., Ltd.	PBR 380	250/125 V, 7.5/15 A, 60Hz, 55 °C	EN 60730-1 EN 60730-2-9	TUV
Thermal Sensor Assembly (Water-in)	James Tech	PB3M-K42D-DW1	3.485 kohm ± 3 % at 50 °C	EN 60335-1 EN 60335-2-84	Tested in appliance
Thermal Sensor Assembly (Water out)	James Tech	PB3M-K42D-DW5	3.485 kohm ± 3 % at 50 °C	EN 60335-1 EN 60335-2-84	Tested in appliance
Sheathed Heating Element	Ga Na Energy Co., Ltd	220V-800W×2 (DIB-1500N)	220V, 800W	EN 60335-1 EN 60335-2-84	Tested in appliance
Insulation Thermal Rubber	Bergquist Co.	400-(hh)#	HB, Min.Thickness 0.25 mm, 150 °C	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)
Thermal fuse	Dong-Yang Electronics Coasdf., Ltd.	DF72S	AC 250 V, 15 A, 72 °C	EN 60691	VDE
Alt.)	Sung Woo Industrial Co.	SW-102T	AC 250 V, 10/15 A, 72 °C	EN 60691	VDE
Sleeving for thermal fuse	Young Chang Silicone Co., Ltd.	Y-SRGT-600+	600 V, 200 °C	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)
<b>Dry assembly</b>					
Material of dry assembly housing	LG CHEMICAL (GUANGZHOU) ENGINEERING PLASTICS CO LTD	SG-175	HB	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)
Lead Wire	Kyunshin Cable Co Ltd	1569	22 AWG, 105 °C, 300 V	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)
Dry fan motor	Zhongshan Hengshan Plastic Products Co., Ltd.	FS75302H	12 V dc, 0.48 A.	EN 60335-1 EN 60335-2-84	Tested in appliance
Heating Element Supporting Plate&cover	Mica Electric Material (Lu He) Co Ltd.	HP5 or HP5J	V-0, min. 0.7 mm thick	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)

IEC 60335-2-84					
Clause	Requirement + Test		Result - Remark		Verdict
Self resetting thermal cut-out	Seki Controls Co.	ST-22	125/250 V, 15/10 A, 105 °C	EN 60730-1 EN 60730-2-3	VDE
Thermal fuse	Dong-Yang Electronics Coasdf., Ltd.	DF152S	AC 250 V, 15 A, 152 °C	EN 60691	VDE
Alt.)	Sung Woo Industrial Co.	SW-116T	AC 250 V, 10/15 A, 152 °C	EN 60691	VDE
Heating Element	Dong Kook Electronics Co., Ltd.	220V 250W	220 V, 250 W	EN 60335-1 EN 60335-2-84	Tested in appliance
<b>EMI PCB part</b>					
AC connector (J2, J3)	Korea Electric Terminal Co., Ltd.	MG640598	250 V, 15 A	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)
Fuse (F1)	Littelfuse Inc.	218015	250 V, 15 A.	EN 60127-1 EN 60127-2	VDE
Line Filter (L1)	Samwon Engineering Co., Ltd.	C27A15	Class 105 (A)	EN 60335-1 EN 60335-2-84	Tested in appliance
Varistor (TNR1)	Amotech	INR10D471	470 V	IEC 61051-1 IEC 61051-2 IEC 61051-2-2 CECC 42000 CECC 42200 CECC 42201	VDE
Alt.)	Centra Science Corp.	CNR10D471K			
Alt.)	Joyin Company Ltd.	JVR10N471K			
Alt.)	Sam Wha Capacitor Co., Ltd.	SVC471D-10A			
Alt.)	Xiamen Wanming	WMR10D471 K			
Varistor (TNR2)	Amotech	INR14D471	470 V	IEC 61051-1 IEC 61051-2 IEC 61051-2-2 CECC 42000 CECC 42200 CECC 42201	VDE
Alt.)	Centra Science Corp.	CNR14D471K			
Alt.)	Joyin Company Ltd.	JVR14N471K			
Alt.)	Sam Wha Capacitor Co., Ltd.	SVC471D-14A			
Alt.)	Xiamen Wanming	WMR14D471 K			
Varistor (TNR3)	Amotech	INR14D182	1800 V	IEC 61051-1 IEC 61051-2 IEC 61051-2-2 CECC 42000 CECC 42200 CECC 42201	VDE
Alt.)	Centra Science Corp.	CNR14D182K			
Alt.)	Joyin Company Ltd.	JVR14N182K			
Alt.)	Sam Wha Capacitor Co., Ltd.	SVC182D-14A			
Alt.)	Xiamen Wanming	WMR14D182 K			
X-Capacitor (C1)	Pilkor	PCX2 335, PCX2 335M or PCX2 337	275 V; 0.1 uF; X2	IEC 60384-14 EN 132400	ENEC-SEMKO
Alt.)	Iskra	KNB 1560			VDE
Alt.)	Shenzhen Su Rong	MPX / MKP			FIMKO
Alt.)	ZhuHai Sung Ho	CMPP			

IEC 60335-2-84					
Clause	Requirement + Test		Result - Remark	Verdict	
Alt.)	Carli Electronics	MPX			
X-Capacitor (C2)	Pilkor	PCX2 335, PCX2 335M or PCX2 337	275 V; 0.47 uF; X2	IEC 60384-14 EN 132400	ENEC-SEMKO
Alt.)	Iskra	KNB 1560			VDE FIMKO
Alt.)	Shenzhen Su Rong	MPX / MKP			
Alt.)	ZhuHai Sung Ho	CMPP			
Alt.)	Carli Electronics	MPX			
Y-Capacitor (C3, C4)	Samwha	SD	250 V; 2200 pF; Y1	IEC 60384-14 EN 132400	VDE FIMKO
Alt.)	Guangdong	F			
Alt.)	Netron Tech	AD			
Alt.)	Hsuan tai	CY			
Alt.)	Dong il	DA			
Alt.)	Success	SE			
Alt.)	Pan overseas	AH			
Alt.)	Jya-Nay	JN			
Alt.)	Du san	NK			
Moulding Compound on PCB	Dong Nam Petroleum Ind Co Ltd.	UF-825A/B	V-0	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)
PCB Bottom Case	LG Chemical Ltd	AF342F	V-0/5VB, min. 2.0 mm thick	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)
Alt.)	LG Chemical Ltd	AF312	V-0, min. 1.5 mm thick	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)
Alt.)	LG Chemical Ltd	410AF(#)	V-0, min. 1.5 mm thick	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)
PCB	COME IN TECH CO LTD	10-V-0	V-0	EN 60335-1 EN 60335-2-84	Tested in appliance
<b>Main PCB Part</b>					
Connector (J14)	Yeon Ho Electronics Co Ltd.	SMW250, SMH250	250 V, 3 A	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)
Fuse (F1)	Save Fusetech	SR-5 or SS-5	T3.15 AL; 250 V	IEC/EN 60127-1 IEC/EN 60127-3	VDE
Alt.)	Orisel	OR 5 or OS5			
Alt.)	Smart Electronics	SPT			
Alt.)	ALPI	AR5			
Alt.)	Littelfuse	663			
Line Filter (T2)	Samwon Engineering	LF20MH (LF1)	Class 105 (A)	EN 60335-1 EN 60335-2-84	Tested in appliance
Optical Isolator (U7)	Kodenshi	PC-17K1	internal: > 4 mm External: > 6 mm Through Insulation:>0.4 mm	Din VDE 0884 EN 60747-5-2 EN 60950-1	FIMKO VDE
Alt.)	Lite-on	LTV 817			
Alt.)	Cosmo	KP1010			
Alt.)	Fairchild	H11A817B			
Alt.)	Everlight Electronics	EL817			
Coupling Capacitor (C36)	Samwha	SD	250 V; 2200 pF; Y1	IEC 60384-14 EN 132400	VDE FIMKO
Alt.)	Guangdong	F			
Alt.)	Netron Tech	AD			

IEC 60335-2-84					
Clause	Requirement + Test		Result - Remark		Verdict
Alt.)	Hsuan tai	CY			
Alt.)	Dong il	DA			
Alt.)	Success	SE			
Alt.)	Pan overseas	AH			
Alt.)	Jya-Nay	JN			
Alt.)	Du san	NK			
Transformer (T1)	Samwon Engineering	580uH	Class 105 (A)	EN 60335-1 EN 60335-2-84	Tested in appliance
Moulding Compound on PCB	Dong Nam Petroleum Ind Co Ltd.	UF-825A/B	V-0	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)
PCB material	COME IN TECH CO LTD	10-V-0	V-0	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)
PCB Bottom Case	LG Chemical Ltd	AF342F	V-0/ 5VB, min. 2.0 mm thick	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)
Alt.)	LG Chemical Ltd	AF312	V-0, min. 1.5 mm thick	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)
Alt.)	LG Chemical Ltd	410AF(#)	V-0, min. 1.5 mm thick	EN 60335-1 EN 60335-2-84	Tested in appliance (UL)
1) An asterisk indicates a mark which assures the agreed level of surveillance					

28.1	TABLE: Threaded part torque test			
Threaded part identification	Diameter of thread (mm)	Column number (I, II, or III)	Applied torque ( Nm )	
Earthing connection screw	3.87	II	1.2	
Enclosure fixing screw	3.85	II	1.2	

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict

29.1	TABLE: Clearances						P
	Overvoltage category... :	II					—
		Type of insulation:					
Rated impulse voltage (V):	Min. cl (mm)	Basic	Functional	Supplementary	Reinforced	Verdict / Remark	
330	0,5*	-	-	-	-	N/A	
500	0,5*	-	-	-	-	N/A	
800	0,5*	-	-	-	-	N/A	
1 500	0,5**	-	-	-	-	N/A	
2 500	1,5**	2.0	2.0	2.0	-	P	
4 000	3,0**	-	-	-	3.5	P	
6 000	5,5**	-	-	-	-	N/A	
8 000	8,0**	-	-	-	-	N/A	
10 000	11,0**	-	-	-	-	N/A	

\*) The value is increased to 0,8mm for pollution degree 3  
 \*) If the construction is affected by wear, distortion, movement of the parts or during assembly, the value is increased by 0,5 mm

29.2	TABLE: Creepage distances, basic, supplementary and reinforced insulation										P
Working voltage (V)	Creepage distance (mm) Pollution degree										Verdict
	1	2			3			Type of insulation			
	Material group			Material group							
		I	II	IIIa/IIIb	I	II	IIIa/IIIb	B*)	S*)	R*)	
≤50	0,2	0,6	0,9	1,2	1,5	1,7	1,9		—	—	N/A
≤50	0,2	0,6	0,9	1,2	1,5	1,7	1,9	—		—	N/A
≤50	0,4	1,2	1,8	2,4	3,0	3,4	3,8	—	—		N/A
>50 and ≤125	0,3	0,8	1,1	1,5	1,9	2,1	2,4		—	—	N/A
>50 and ≤125	0,3	0,8	1,1	1,5	1,9	2,1	2,4	—		—	N/A
>50 and ≤125	0,6	1,6	2,2	3,0	3,8	4,2	4,8	—	—		N/A
>125 and ≤250	0,6	1,3	1,8	<u>2,5</u>	3,2	3,6	4,0	2.5	—	—	P
>125 and ≤250	0,6	1,3	1,8	<u>2,5</u>	3,2	3,6	4,0	—	2.5	—	P
>125 and ≤250	1,2	2,6	3,6	<u>5,0</u>	6,4	7,2	8,0	—	—	5.0	P
>250 and ≤400	1,0	2,0	2,8	4,0	5,0	5,6	6,3		—	—	N/A



IEC 60335-2-84											
Clause	Requirement + Test							Result - Remark			Verdict
>250 and ≤400	1,0	2,0	2,8	4,0	5,0	5,6	6,3	—	—	—	N/A
>250 and ≤400	2,0	4,0	5,6	8,0	10,0	11,2	12,6	—	—	—	N/A
>400 and ≤500	1,3	2,5	3,6	5,0	6,3	7,1	8,0	—	—	—	N/A
>400 and ≤500	1,3	2,5	3,6	5,0	6,3	7,1	8,0	—	—	—	N/A
>400 and ≤500	2,6	5,0	7,2	10,0	12,6	14,2	16,0	—	—	—	N/A
>500 and ≤800	1,8	3,2	4,5	6,3	8,0	9,0	10,0	—	—	—	N/A
>500 and ≤800	1,8	3,2	4,5	6,3	8,0	9,0	10,0	—	—	—	N/A
>500 and ≤800	3,6	6,4	9,0	12,6	16,0	18,0	20,0	—	—	—	N/A
>800 and ≤1000	2,4	4,0	5,6	8,0	10,0	11,0	12,5	—	—	—	N/A
>800 and ≤1000	2,4	4,0	5,6	8,0	10,0	11,0	12,5	—	—	—	N/A
>800 and ≤1000	4,8	8,0	11,2	16,0	20,0	22,0	25,0	—	—	—	N/A
>1000 and ≤1250	3,2	5,0	7,1	10,0	12,5	14,0	16,0	—	—	—	N/A
>1000 and ≤1250	3,2	5,0	7,1	10,0	12,5	14,0	16,0	—	—	—	N/A
>1000 and ≤1250	6,4	10,0	14,2	20,0	25,0	28,0	32,0	—	—	—	N/A
>1250 and ≤1600	4,2	6,3	9,0	12,5	16,0	18,0	20,0	—	—	—	N/A
>1250 and ≤1600	4,2	6,3	9,0	12,5	16,0	18,0	20,0	—	—	—	N/A
>1250 and ≤1600	8,4	12,6	18,0	25,0	32,0	36,0	40,0	—	—	—	N/A
>1600 and ≤2000	5,6	8,0	11,0	16,0	20,0	22,0	25,0	—	—	—	N/A
>1600 and ≤2000	5,6	8,0	11,0	16,0	20,0	22,0	25,0	—	—	—	N/A
>1600 and ≤2000	11,2	16,0	22,0	32,0	40,0	44,0	50,0	—	—	—	N/A
>2000 and ≤2500	7,5	10,0	14,0	20,0	25,0	28,0	32,0	—	—	—	N/A
>2000 and ≤2500	7,5	10,0	14,0	20,0	25,0	28,0	32,0	—	—	—	N/A
>2000 and ≤2500	15,0	20,0	28,0	40,0	50,0	56,0	64,0	—	—	—	N/A
>2500 and ≤3200	10,0	12,5	18,0	25,0	32,0	36,0	40,0	—	—	—	N/A
>2500 and ≤3200	10,0	12,5	18,0	25,0	32,0	36,0	40,0	—	—	—	N/A
>2500 and ≤3200	20,0	25,0	36,0	50,0	64,0	72,0	80,0	—	—	—	N/A
>3200 and ≤4000	12,5	16,0	22,0	32,0	40,0	45,0	50,0	—	—	—	N/A
>3200 and ≤4000	12,5	16,0	22,0	32,0	40,0	45,0	50,0	—	—	—	N/A
>3200 and ≤4000	25,0	32,0	44,0	64,0	80,0	90,0	100,0	—	—	—	N/A
>4000 and ≤5000	16,0	20,0	28,0	40,0	50,0	56,0	63,0	—	—	—	N/A
>4000 and ≤5000	16,0	20,0	28,0	40,0	50,0	56,0	63,0	—	—	—	N/A
>4000 and ≤5000	32,0	40,0	56,0	80,0	100,0	112,0	126,0	—	—	—	N/A
>5000 and ≤6300	20,0	25,0	36,0	50,0	63,0	71,0	80,0	—	—	—	N/A
>5000 and ≤6300	20,0	25,0	36,0	50,0	63,0	71,0	80,0	—	—	—	N/A

IEC 60335-2-84											
Clause	Requirement + Test							Result - Remark			Verdict
>5000 and ≤6300	40,0	50,0	72,0	100,0	126,0	142,0	160,0	—	—		N/A
>6300 and ≤8000	25,0	32,0	45,0	63,0	80,0	90,0	100,0		—	—	N/A
>6300 and ≤8000	25,0	32,0	45,0	63,0	80,0	90,0	100,0	—		—	N/A
>6300 and ≤8000	50,0	64,0	90,0	126,0	160,0	180,0	200,0	—	—		N/A
>8000 and ≤10000	32,0	40,0	56,0	80,0	100,0	110,0	125,0		—	—	N/A
>8000 and ≤10000	32,0	40,0	56,0	80,0	100,0	110,0	125,0	—		—	N/A
>8000 and ≤10000	64,0	80,0	112,0	160,0	200,0	220,0	250,0	—	—		N/A
>10000 and ≤12500	40,0	50,0	71,0	100,0	125,0	140,0	160,0		—	—	N/A
>10000 and ≤12500	40,0	50,0	71,0	100,0	125,0	140,0	160,0	—		—	N/A
>10000 and ≤12500	80,0	100,0	142,0	200,0	250,0	280,0	320,0	—	—		N/A
*) , B=Basic, S=Supplementary and R=Reinforced											

IEC 60335-2-84			
Clause	Requirement + Test	Result - Remark	Verdict

29.2	TABLE: Creepage distances, functional insulation							P
Working voltage (V)	Creepage distance (mm) Pollution degree							Verdict / Remark
	1	2			3			
	Material group			Material group				
	I	II	IIIa/IIIb	I	II	IIIa/IIIb		
≤50	0,2	0,6	0,8	1,1	1,4	1,6	1,8	N/A
>50 and ≤125	0,3	0,7	1,0	1,4	1,8	2,0	2,2	N/A
>125 and ≤250	0,4	1,0	1,4	<u>2,0</u>	2,5	2,8	3,2	P
>250 and ≤400	0,8	1,6	2,2	3,2	4,0	4,5	5,0	N/A
>400 and ≤500	1,0	2,0	2,8	4,0	5,0	5,6	6,3	N/A
>500 and ≤800	1,8	3,2	4,5	6,3	8,0	9,0	10,0	N/A
>800 and ≤1000	2,4	4,0	5,6	8,0	10,0	11,0	12,5	N/A
>1000 and ≤1250	3,2	5,0	7,1	10,0	12,5	14,0	16,0	N/A
>1250 and ≤1600	4,2	6,3	9,0	12,5	16,0	18,0	20,0	N/A
>1600 and ≤2000	5,6	8,0	11,0	16,0	20,0	22,0	25,0	N/A
>2000 and ≤2500	7,5	10,0	14,0	20,0	25,0	28,0	32,0	N/A
>2500 and ≤3200	10,0	12,5	18,0	25,0	32,0	36,0	40,0	N/A
>3200 and ≤4000	12,5	16,0	22,0	32,0	40,0	45,0	50,0	N/A
>4000 and ≤5000	16,0	20,0	28,0	40,0	50,0	56,0	63,0	N/A
>5000 and ≤6300	20,0	25,0	36,0	50,0	63,0	71,0	80,0	N/A
>6300 and ≤8000	25,0	32,0	45,0	63,0	80,0	90,0	100,0	N/A
>8000 and ≤10000	32,0	40,0	56,0	80,0	100,0	110,0	125,0	N/A
>10000 and ≤12500	40,0	50,0	71,0	100,0	125,0	140,0	160,0	N/A


## IEC 60335-2-84

TABLE 30 RESISTANCE TO HEAT, FIRE AND TRACKING (appended table)														
Component	Manufacturer	Type	Ball pressure test				Tracking test [CTI/ PTI]	Glow wire test					Needle-flame test	Verdict
			75°C	cl. 11 +40°C	125°C	cl. 19 +25°C		GWT 550°C	GWT 650°C	GWT 750°C	GWFI 850°C	GWIT		
Main Enclosure, Toilet seat, Seat cover	LG CHEMICAL (GUANGZHOU) ENGINEERING PLASTICS CO LTD	SG-175	1.0 mm	-	-	-	-	P	-	-	-	-	-	P
AC Connector (J2, J3)	Korea Electric Ter minal Co., Ltd.	MG640598	-	-	1.4 mm	-	-	-	-	P	850°C ignition (8s)	-	P Surrounding part (V-0)	P
PCB bottom Case & Dry part housing	LG Chemical Ltd.	AF342F	-	-	1.0 mm	-	-	-	-	P	P	-	-	P
Alt.)	LG Chemical Ltd	AF312		-	1.0 mm			-	-	P	P	-	-	P
Alt.)	LG Chemical Ltd	410AF(#)		-	1.0 mm			-	-	P	P	-	-	P
Connector	Yeon Ho	SMW250	-	-	1.2 mm	-	-	-	-	P	850°C ignition (5s)	-	P Surrounding part (V-0)	P
Linefilter bobbin (T2)	HEXION SPECIAL TY CHEMICALS G MBH	PF2736(a)(b)	-	-	0.8 mm	-	-	-	-	P	P	-	-	P
Transformer bobbin (T1)	HEXION SPECIAL TY CHEMICALS G MBH	PF2736(a)(b)	-	-	0.8 mm	-	-	-	-	P	P	-	-	P




IEC 60335-2-84

Wiring diagram



IEC 60335-2-84


Wiring diagram





IEC 60335-2-84



Wiring diagram






IEC 60335-2-84

Circuit diagram



IEC 60335-2-84

Circuit diagram



IEC 60335-2-84

Photos – model DIB-2000, HDB-1500R





IEC 60335-2-84

Photos – model DIB-2000, HDB-1500R



IEC 60335-2-84

Photos – model DIB-2000, HDB-1500R





IEC 60335-2-84

Photos – model DIB-2000, HDB-1500R




IEC 60335-2-84

Photos – DIB-2000, HDB-1500R



IEC 60335-2-84

Photos – model DIB-2000, HDB-1500R






IEC 60335-2-84

Photos – model HDB-2500R





IEC 60335-2-84

Photos – model HDB-2500R



IEC 60335-2-84

Photos – model HDB-2500R



IEC 60335-2-84

Photos – model HDB-1500




IEC 60335-2-84

Photos – model HDB-1500





IEC 60335-2-84

Photos – model HDB-1500



IEC 60335-2-84

Photos – model HDB-1500



-End of Test Report-



# Attachment No. 1

**Amendment A14:2010 to EN 60335-1:2002**

**Household and similar electrical appliances – Safety  
Part 1: General requirements**

***Attachment contains***

Cover page:	1 page
Requirements:	10 pages
Total:	11 pages

Explanation for Abbreviations:

Possible Verdicts: **P** = Pass, **F**= Fail, **N/A** = Not Applicable

Remarks:

Throughout this report, a comma (point) is used as the decimal separator.



Amendment A14:2010 to EN 60335-1:2002			
Clause	Requirement - Test	Result - Remark	Verdict
	<b>CENELEC COMMON MODIFICATIONS (EN)</b>		
6.1	Delete "class 0" and "class 01"		N/A
7.1	Single-phase appliances to be connected to the supply mains: 230 V covered	220 – 240 V	P
	Multi-phase appliances to be connected to the supply mains: 400 V covered		N/A
19.14	If a relay or contactor with more than one contact is used, all contacts are short-circuited at the same time		P
24.1	Unless otherwise specified, the requirements of Clause 29 apply between live parts of components and accessible parts of the appliance		P
	Unless otherwise specified, the requirements of 30.2 apply to parts of non-metallic material in components including parts of non-metallic material supporting current-carrying connections inside components		P
	Components that have not been tested or do not comply with the relevant component standard are tested according to the requirements of 30.2		P
	Where the relevant standard for lampholders and starterholders specifies gauging and interchangeability requirements at elevated temperatures, the temperature measured during the tests of Clause 11 are used		N/A
24.1.7	If the remote operation of the appliance is via a telecommunication network, the relevant standards for the telecommunication interface circuitry in the appliance are EN 41003 and EN 60950-1:2006, subclause 6.3	No such appliance	N/A
25.6	Supply cords of single-phase portable appliances having a rated current not exceeding 16 A, fitted with a plug complying with the following standard sheets of IEC 60083:1975:		-
	- for Class I appliances: standard sheet C2b, C3b or C4.....:		P
	- for Class II appliances: standard sheet C5 or C6 .....		N/A
25.7	Rubber sheathed cords (60245 IEC 53) are not suitable for appliances intended to be used outdoors or when they are liable to be exposed to significant amount of ultraviolet radiation		N/A
	Additional type of supply cord:		-
	- ordinary polychloroprene sheathed flexible cord (60245 IEC 57)		N/A
	Supply cords having high flexibility, not lighter than:		-

Amendment A14:2010 to EN 60335-1:2002			
Clause	Requirement - Test	Result - Remark	Verdict
	- rubber insulated and sheathed cord (60245 IEC 86)		N/A
	- rubber insulated, crosslinked PVC sheathed cord (60245 IEC 87)		N/A
	- crosslinked PVC insulated and sheathed cord (60245 IEC 88)		N/A
26.2	Conductors connected by soldering are not considered to be positioned or fixed so that reliance is not placed upon the soldering alone to maintain it in position unless they are held in place near the terminals independently of the solder		N/A
26.11	Conductors connected by soldering are not considered to be positioned or fixed so that reliance is not placed upon the soldering alone to maintain it in position unless they are held in place near the terminals independently of the solder		N/A
29.2	In a double insulation system, the working voltage for both the basic insulation and supplementary insulation is taken as the working voltage across the complete double insulation system		N/A
29.3	The third dashed item replaced by: - an assessment of the thermal quality of the material combined with an electric strength test, in accordance with 29.3.3, and, for accessible reinforced insulation consisting of a single layer, measurement in accordance with 29.3.Z1		N/A
29.3.Z1	For accessible reinforced insulation consisting of a single layer, the thickness of the layer complies with table Z1; rated voltage (V); overvoltage category; thickness (mm):		N/A
32	Compliance regarding electromagnetic fields is checked according to EN 50366 or EN 62233	EN 62233	P

<b>ZA</b>	<b>ANNEX ZA (NORMATIVE), SPECIAL NATIONAL CONDITIONS (EN)</b>		-
	<b>Denmark</b>		-
7.12	Requirements regarding marking tag of power supply cord and connection of earthing wire for class I appliances delivered without a plug		N/A
	<b>Norway</b>		-
19.5	The test is also applicable to appliances intended to be permanently connected to fixed wiring		N/A
	<b>France and Norway</b>		-

Amendment A14:2010 to EN 60335-1:2002			
Clause	Requirement - Test	Result - Remark	Verdict
22.2	The second paragraph of this subclause, dealing with single-phase, permanently connected class I appliances having heating elements, is not applicable due to the supply system		N/A
	<b>Belgium, France, Spain and United Kingdom</b>		-
25.6	Plugs according to standard sheet C2b not allowed		N/A
	<b>Austria, Finland, Germany, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom</b>		-
25.6	Plugs according to standard sheet C3b not allowed		N/A
	<b>Denmark</b>		-
25.6	Supply cords of single-phase portable appliances having a rated current not exceeding 13 A provided with a plug according to the following:		N/A
	Class I appliances: Section 107-2-D1, ed.3 1998, Standard Sheet DK 2-1a		N/A
	For appliances covered by a Part 2 of EN 60335, also plugs in accordance with Section 107-2-D1, ed. 3, 1998, Standard Sheet C2b, C3b or C4 are allowed		N/A
	Class II appliances: Section 107-2-D1, ed.3 1998, Standard Sheet C1b, C5, C6, DKA 2-1a and DKA 2-1b		N/A
	Stationary single-phase appliances, having a rated current not exceeding 13 A, and provided with a supply cord and a plug, the plug is in accordance with the requirements above		N/A
	Multi-phase appliances and single-phase appliances having a rated current exceeding 13 A, and provided with a supply cord and a plug, the plug is in accordance with the requirements below:		N/A
	Class I appliances: Section 107-2-D1, Standard Sheet DK 6-1a / EN 60309-2, Standard Sheet 2-II, 2-IV		N/A
	Class II appliances: Section 107-2-D1, Standard Sheet DK 6-1a / EN 60309-2, Standard Sheet 2-II, 2-IV, the earthing contact not being connected		N/A
	The current for the plug not exceeding the values specified; standard sheet (no.); current (A) :		N/A

Amendment A14:2010 to EN 60335-1:2002			
Clause	Requirement - Test	Result - Remark	Verdict
	<b>Ireland</b>		-
25.6	Only plugs according to Standard Sheets B2 and C5 allowed		N/A
	<b>Italy</b>		-
25.6	Only plugs listed in GENELEC Report R0BT-005:2001 allowed		N/A
	<b>Spain</b>		-
25.6	For appliances for household use, only the following plugs are allowed:		N/A
	according to UNE 20315: ESC 10-1b, C2b, C4, C6 or ESB 25-5b		N/A
	according to UNE-EN 50075		N/A
	<b>Switzerland</b>		-
25.6	Supply cords of portable household and similar electrical appliances having a rated current not exceeding 10 A, provided with a plug complying with SEV 1011 or IEC 60884-1 and one of the following dimension sheets:		N/A
	SEV 6532-2.1991, plug type 15, 3P+N+PE, 250/400 V, 10 A		N/A
	SEV 6533-2.1991, plug type 11, L+N, 250 V, 10 A		N/A
	SEV 6534-2.1991 plug type 12, L+N+PE, 250 V, 10 A		N/A
	<b>United Kingdom</b>		-
25.6	Only plugs according to Standard Sheets B2 and C5 allowed		P
	<b>Ireland and United Kingdom</b>		-
25.8	Replacement of figures (rated current/cross-sectional area) in the table		N/A
<b>ZB</b>	<b>ANNEX ZB (INFORMATIVE), NATIONAL DEVIATIONS (EN)</b>		-
	<b>Switzerland</b>		-
4	Information about batteries with carbon-zinc and alkali-manganese		N/A

Amendment A14:2010 to EN 60335-1:2002			
Clause	Requirement - Test	Result - Remark	Verdict
	<b>Italy</b>		-
7.1	The voltage is 220 V/380 V		N/A
	<b>Ireland</b>		-
25.6	These regulations apply to all plugs for domestic use at a voltage of not less than 200 V and allow only plugs complying with I.S. 401:1997, or equivalent, to be fitted to domestic appliances.		N/A
	<b>United Kingdom</b>		-
25.6	These regulations apply to all plugs for domestic use at a voltage of not less than 200 V and allow only plugs to BS 1363 to be fitted to domestic appliances. It also allows plugs to BS 4573 and standard sheet C5 to be fitted to shavers and toothbrushes.		N/A
	<b>Germany</b>		-
29.3	Third dashed item not applicable for appliances where the insulation is accessible. Additional measures, such as a multi-layered insulation or adequate thickness, taken.		N/A
<b>ZC</b>	<b>ANNEX ZC (NORMATIVE)</b> NORMATIVE REFERENCES TO INTERNATIONAL PUBLICATIONS WITH THEIR CORRESPONDING EUROPEAN PUBLICATIONS		-
	A list of referenced documents in this standard		P
<b>ZD</b>	<b>ANNEX ZD (INFORMATIVE)</b> IEC and CENELEC CODE DESIGNATIONS FOR FLEXIBLE CORDS		-
	A list of code designations for different types of flexible cords		P
<b>ZE</b>	<b>ANNEX ZE (INFORMATIVE)</b> SPECIFIC ADDITIONAL REQUIREMENTS FOR APPLIANCES AND MACHINES INTENDED FOR COMMERCIAL USE	No commercial use	-
7.1	Business name and full address of the manufacturer and, where applicable, his authorized representative.....:		N/A
	Model or type reference.....:		N/A

Amendment A14:2010 to EN 60335-1:2002			
Clause	Requirement - Test	Result - Remark	Verdict
	Serial number, if any.....:		N/A
	Production year		N/A
	Designation of the appliance .....		N/A
7.12	Instructions provided with the appliance so that the appliance can be used safely		N/A
	The instructions contain at least the following information:		-
	- the business name and full address of the manufacturer and, where applicable, his authorized representative		N/A
	- model or type reference of the appliance as marked on the appliance itself, except for the serial number		N/A
	- the designation of the appliance together with its explanation in case it is given by a combination of letters and/or numbers		N/A
	- the general description of the appliance, when needed due to the complexity of the appliance		N/A
	- specific precautions if required during installation, operation, adjusting, user maintenance, cleaning, repairing or moving		N/A
	- when needed drawings, diagrams, descriptions and explanations necessary for the safe use and user maintenance of the appliance		N/A
	- the possible reasonably foreseeable misuse and, whenever relevant, a warning against the effects it may have on the safe use of the appliance		N/A
	The words "Original instructions" appear on the language version(s) verified by the manufacturer or by the authorized representative		N/A
	When a translation of the original instructions has been provided by a person introducing the appliance on the market; the meaning of the sentence "Translation of the original instructions" appear in the relevant instructions delivered with the appliance		N/A
	The instructions for maintenance/service to be done by specialized personnel, mandated by the manufacturer or the authorized representative may be supplied in only one Community language which the specialized personnel understand		N/A
	The instructions indicate the type and frequency of inspections and maintenance required for safe operation including the preventive maintenance measures		N/A
7.12.Z1	Wherever needed for specific appliances, the following information to be given:		-

Amendment A14:2010 to EN 60335-1:2002			
Clause	Requirement - Test	Result - Remark	Verdict
	- on use, transportation, assembly, dismantling when out of service, testing or foreseeable breakdowns, if these operations have consequences on stability of the appliance in order to avoid overturning, falling or uncontrolled movements of the appliance or of its component parts		N/A
	- on how to maintain adequate mechanical stability when in use, during transportation, assembly, dismantling, scrapping and any other action involving the appliance		N/A
	- on the protective measures to be taken by the user, including, where appropriate, the personal protective equipment to be provided		N/A
	- on the operating method to be followed in the event of accident or breakdown; if a blockage is likely to occur the operating method to safely unblock the appliance		N/A
	- on the specifications on the spare parts to be used, when these affect the health and safety of the operator		N/A
	- on airborne noise emissions, determined and declared in accordance with the relevant Part 2		N/A
	This includes:		-
	- the A-weighted emission sound pressure level at workstations, where this exceeds 70 dB(A) .....		N/A
	- where this level does not exceed 70 dB(A), this fact is indicated		N/A
	- the peak C-weighted instantaneous sound pressure value at workstations, where this exceeds 63 Pa (130 Db in relation to 20 µPa) .....		N/A
	- the A-weighted sound power level emitted by the machinery, where the A-weighted emission sound pressure level at workstations exceeds 80 Db(A) .:		N/A
19.11.4.8	The appliance continues to operate, without causing any hazard to the user, from the same point in its operating cycle at which the voltage fluctuation occurred, or		N/A
	a manual operation is required to restart it		N/A
20.1	Appliances and their components and fittings have adequate mechanical stability during transportation, assembly, dismantling and any other action involving the appliance		N/A
20.2	Dangerous moving transmission parts safeguarded either by design or guards		N/A
	When guards are used, they are fixed guards, interlocking movable guards or protective devices		N/A

Amendment A14:2010 to EN 60335-1:2002			
Clause	Requirement - Test	Result - Remark	Verdict
	Moving parts directly involved in the function of the appliance which cannot be made completely inaccessible fitted with:		-
	- fixed guards or interlocking movable guards preventing access to those sections of the parts that are not used in the work, and		N/A
	- adjustable guards restricting access to those sections of the moving parts where access is necessary		N/A
	Interlocking movable guards used where frequent access is required		N/A
21.1	Appliances and their components and fittings have adequate mechanical strength and is constructed to withstand such rough handling that may be expected in normal use, during transportation, assembly, dismantling, scrapping and any other action involving the appliance		N/A
22.ZE.1	For appliances provided with a seat, the seat gives adequate stability		N/A
	The distance between the seat and the control devices capable of being adapted to the operator		N/A
22.ZE.2	For appliances provided with separate devices for the start and the stop functions, the stop function is unambiguously identifiable and does always override the start function		N/A
	For appliances provided with one device performing the start and the stop function, the stop function is unambiguously identifiable and does always override the start function		N/A
22.ZE.3	Appliances designed in such a way that incorrect mounting is avoided, if this can lead to an unsafe situation		N/A
	If this is not possible, information on the correct mounting is given directly on the part and/or the enclosure		N/A
22.ZE.4	Where the weight, size or shape prevents appliances from being moved manually, they are fitted with attachments for lifting gear, or		N/A
	so designed that they can be fitted with such attachments, or		N/A
	be shaped in such a way that standard lifting gear can easily be used		N/A
	Appliances to be moved manually are constructed or equipped so that they can be moved easily and safely		N/A
22.ZE.5	The fixing systems of fixed guards which prevent access to dangerous moving transmission parts only removable with the use of tools		N/A



Amendment A14:2010 to EN 60335-1:2002			
Clause	Requirement - Test	Result - Remark	Verdict
	If such guards have to be removed frequently their fixing systems remain attached to the fixed guards or to the machine after removal		N/A
	Where possible, guards are incapable of remaining in place without their fixings		N/A
	This does not apply if, after removal of the screws, or if the component is incorrectly repositioned, the appliance becomes inoperative		N/A
	If movable guards are interlocked, the interlocking devices prevent the start of hazardous appliance functions until the guards are fixed in their position, and give a stop command whenever they are no longer closed		N/A
	Where it is possible for an operator to reach the danger zone before the risk due to hazardous appliance functions has ceased, movable guards associated with a guard locking device in addition to an interlocking device that:		-
	- prevents the start of hazardous appliance functions until the guard is closed and locked, and		N/A
	- keeps the guard closed and locked until the risk of injury from the hazardous appliance functions has ceased		N/A
	Interlocking movable guards remain attached to the appliance when open and they are designed and constructed in such a way that they can be adjusted only by means of an intentional action		N/A
	Interlocking movable guards designed in such a way that the absence or failure of one of their components prevents starting or stops the hazardous appliance functions		N/A
	Compliance is checked by inspection and by the tests as specified		N/A
	After this test any defect that may be expected in normal use is applied to the interlock system, including interruption of the supply, only one defect being simulated at a time		N/A
	After these tests the interlock system is fit for further use		N/A
	Adjustable guards restricting access to those areas of the moving parts strictly necessary for the work are:		-
	- adjustable manually or automatically, depending on the type of work involved, and		N/A
	- readily adjustable without the use of tools		N/A
22.ZE.6	In case of interruption, re-establishment after an interruption or fluctuation in whatever manner of the power supply, the appliance does not restart		N/A

Amendment A14:2010 to EN 60335-1:2002			
Clause	Requirement - Test	Result - Remark	Verdict
	However, automatic restarting of the operation is allowed if the appliance may continue to operate, without causing any hazard to the user, from the same point in its operating cycle at which the voltage interruption or fluctuation occurred		N/A
<b>ZF</b>	<b>ANNEX ZF (INFORMATIVE)</b> CRITERIA APPLIED FOR THE ALLOCATION OF PRODUCTS COVERED BY STANDARDS IN THE EN 60335 SERIES UNDER LVD OR MD		-
	A list of standards under GENELEC/TC61 with the consequent allocation of standards under LVD or MD	LVD	P
<b>ZZ</b>	<b>ANNEX ZZ (INFORMATIVE)</b> COVERAGE OF ESSENTIAL REQUIREMENTS OF EC DIRECTIVES		-
	Description of the background for the European standard EN 60335-1/A14:2010		P

<b>Annex EN 62233:2008</b>			
Clause	Requirement + Test	Result - Remark	Verdict
<b>EMF- ELECTROMAGNETICS FIELDS</b>			
	The tested product also complies with the requirements of EN 62233:2008		
	Limit .....100%	Measured max. 26.96.%	P

**- End of Test Report -**

<b>ATTACHMENT 2 TO TEST REPORT IEC 60335_2_82B</b> <b>EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES</b> (Household and similar electrical appliances - Safety) Part 2: Particular requirements for amusement machines and personal service machines)	
<b>Differences according to</b> .....	EN 60335-2-82:2003 +A1:2008 in conjunction with EN 60335-1:2002 +A1:2004 +A11:2004 +A2:2006 +A12:2006 EN 50366:2003 +A1:2006
<b>Attachment Form No.</b> .....	EU_GD_IEC60335_2_82B
<b>Attachment Originator</b> .....	OVE
<b>Master Attachment</b> .....	Dated 2008-07
<b>Copyright © 2008 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.</b>	

EN 50366			
Clause	Requirement + Test	Result - Remark	Verdict
EMF - ELECTROMAGNETIC FIELDS			
	The tested product also complies to the requirements of EN 50366:2003 + A1:2006		—
	Limit ..... 100%	Measured max. : .. %	N/A



EN 60335-2-82			
Clause	Requirement + Test	Result - Remark	Verdict
6	CLASSIFICATION		—
6.1	Protection against electric shock: Class I, II, III .....:	Class: <u>I</u>	P
7	MARKING AND INSTRUCTIONS		—
7.1	Single-phase appliances to be connected to the supply mains: Rated voltage (range) 230 V covered	220 – 240 V	P
	Multi-phase appliances to be connected to the supply mains: Rated voltage (range) 400 V covered		N/A
25	SUPPLY CONNECTION AND EXTERNAL FLEXIBLE CORDS		—
25.6	Supply cords of single-phase portable appliances having a rated current not exceeding 16 A, fitted with a plug complying with the following standard sheets of IEC 60083:1975 and/or Special National Conditions (Annex ZA):		—
	- standard sheet C2b, C3b or C4 of IEC 60083:1975 for Class I appliances .....		P
	- standard sheet C5 or C6 for Class II appliances .....		N/A
25.7	Additional type of supply cord: (See also code designations at informative Annex ZD of EN-Standard)		—
	- ordinary polychloroprene sheathed flexible cord (H05RN-F)		N/A
25.7	Supply cords having high flexibility, not lighter than:		—
	- rubber insulated and sheathed cord (H03RR-H)		N/A
	- rubber insulated, crosslinked PVC sheathed cord (H03RV4-H)		N/A
	- crosslinked PVC insulated and sheathed cord (H03V4V4-H)		N/A
29.3	The third dashed item replaced by: - an assessment of the thermal quality of the material combined with an electric strength test, in accordance with 29.3.3, and, for accessible reinforced insulation consisting of a single layer, measurement in accordance with 29.3.Z1		P
29.3.Z1	For accessible reinforced insulation consisting of a single layer, the thickness of the layer complies with table Z1; rated voltage (V); overvoltage category; thickness (mm) .....		N/A

EN 60335-2-82			
Clause	Requirement + Test	Result - Remark	Verdict
Annex ZA	ANNEX ZA (NORMATIVE) SPECIAL NATIONAL CONDITIONS		—
<b>Austria</b>			
25.6	Plugs according to standard sheet C3b not allowed		N/A
<b>Belgium</b>			
25.6	Plugs according to standard sheet C2b not allowed		N/A
<b>Denmark</b>			
7.12	Requirements regarding marking tag of power supply cord and connection of earthing wire for class I appliances delivered without a plug		N/A
25.6	Supply cords of single-phase portable appliances having a rated current not exceeding 13 A provided with a plug according to the following:		N/A
	Class I appliances: Section 107-2-D1, ed.3 1998, Standard Sheet DK 2-1a		N/A
	For appliances covered by a Part 2 of EN 60335, also plugs in accordance with Section 107-2-D1 ed.3, 1998, Standard Sheet C2b, C3b or C4 are allowed		N/A
	Class II appliances: Section 107-2-D1, ed.3 1998, Standard Sheet C1b, C5, C6, DKA 2-1a and DKA 2-1b		N/A
	Stationary single-phase appliances, having a rated current not exceeding 13 A, and provided with a supply cord and a plug, the plug is in accordance with the requirements above		N/A
	Multi-phase appliances and single-phase appliances having a rated current exceeding 13 A, and provided with a supply cord and a plug, the plug is in accordance with the requirements below:		N/A
	Class I appliances: Section 107-2-D1, Standard Sheet DK 6-1a / EN 60309-2, Standard Sheet 2-II, 2-IV		N/A
	Class II appliances: Section 107-2-D1, Standard Sheet DK 6-1a / EN 60309-2, Standard Sheet 2-II, 2-IV, earthing contact not connected		N/A

EN 60335-2-82			
Clause	Requirement + Test	Result - Remark	Verdict
<b>Finland</b>			
25.6	Plugs according to standard sheet C3b not allowed		N/A
<b>France</b>			
22.2	The second paragraph of this subclause, dealing with single-phase, permanently connected class I appliances having heating elements, is not applicable due to the supply system		N/A
25.6	Plugs according to standard sheet C2b not allowed		N/A
<b>Germany</b>			
25.6	Plugs according to standard sheet C3b not allowed		N/A
<b>Iceland</b>			
25.6	Plugs according to standard sheet C3b not allowed		N/A
<b>Ireland</b>			
25.6	Plugs according to standard sheet C3b not allowed		N/A
	Only plugs according to Standard Sheets B2 and C5 allowed		N/A
25.8	Replacement of figures (rated current/cross-sectional area) in the table		N/A
<b>Italy</b>			
7.1	The voltage is 220 V/380 V		N/A
25.6	Plugs according to standard sheet C3b not allowed		N/A
	Only plugs listed in CENELEC Report R0BT-005:2001 allowed		N/A

EN 60335-2-82			
Clause	Requirement + Test	Result - Remark	Verdict
<b>Luxembourg</b>			
25.6	Plugs according to standard sheet C3b not allowed		N/A
<b>Netherlands</b>			
25.6	Plugs according to standard sheet C3b not allowed		N/A
<b>Norway</b>			
19.5	The test is also applicable to appliances intended to be permanently connected to fixed wiring		N/A
22.2	The second paragraph of this subclause, dealing with single-phase, permanently connected class I appliances having heating elements, is not applicable due to the supply system		N/A
25.6	Plugs according to standard sheet C3b not allowed		N/A
<b>Portugal</b>			
25.6	Plugs according to standard sheet C3b not allowed		N/A
<b>Spain</b>			
25.6	Plugs according to standard sheet C2b not allowed		N/A
	Plugs according to standard sheet C3b not allowed		N/A
	For appliances for household use, only the following plugs are allowed:		N/A
	- according to UNE 20315: ESC 10-1b, C2b, C4, C6 or ESB 25-5b		N/A
	- according to UNE-EN 50075		N/A
<b>Sweden</b>			
25.6	Plugs according to standard sheet C3b not allowed		N/A

EN 60335-2-82			
Clause	Requirement + Test	Result - Remark	Verdict

<b>Switzerland</b>			
25.6	Plugs according to standard sheet C3b not allowed		N/A
	Supply cords of portable household and similar electrical appliances having a rated current not exceeding 10 A, provided with a plug complying with SEV 1011 or IEC 60884-1 and one of the following dimension sheets:		N/A
	SEV 6532-2.1991, plug type 15, 3P+N+PE, 250/400 V, 10 A		N/A
	SEV 6533-2.1991, plug type 11, L+N, 250 V, 10 A		N/A
	SEV 6534-2.1991 plug type 12, L+N+PE, 250 V, 10 A		N/A
<b>United Kingdom</b>			
25.6	Plugs according to standard sheet C2b not allowed		N/A
	Plugs according to standard sheet C3b not allowed		N/A
	Only plugs according to Standard Sheets B2 and C5 allowed		N/A
25.8	Replacement of figures (rated current/cross-sectional area) in the table		N/A

-End of Test Report-